

544 P WHEEL LOADER

Exeter Township

19-Dec-22

Code	Description
------	-------------

6030DW	544 P WHEEL LOADER
--------	--------------------

Option Codes

2605	English Decals and Manuals
1010	Standard Wheel Loader
0924	John Deere PowerTech Engine John Deere PowerTech PVS 6.8L meets EPA FT4 and EU Stage IV Emissions (166 Net Peak hp) Turbocharged Wet Sleeve Cylinder Liners Automatic Glow Plugs Programmable Auto-Idle and Auto-Shutdown Selected Idle Adjustment from 900-1250 RPM Starter Protection 4 Valves/Cylinder Cooled Exhaust Gas Recirculation Automatic Derating for Exceeded System Temperatures Electronically Controlled HPCR Fuel Delivery System, B20 Biodiesel Compatible Electrical Fuel Priming System Serpentine Drive Belt with Automatic Tensioner Under Hood Dual Element Air Cleaner with Restriction Indicator Under Hood Exhaust Filter and Catalysts with Curved Exhaust Stack Automatic Exhaust Filter Regeneration Dual-Stage Fuel Filter and Water Separator 500 Hour Vertical Spin-on Oil Filter Cartridge Type Oil Crankcase Filter Automatic Engine Cool-down Timer Remote Start Battery Terminals
1520	Automatic Reversing Hydraulic Fan Hydraulically driven fan with proportional fan speed control based on cooling demands to save fuel and reduce noise. Automatic Reversing fan to purge debris and dust on cooling system inlet screens and coolers periodically to reduce cleaning. Reversing intervals can be set in the monitor.
1430	Engine Air Intake System with Centrifugal Precleaner
1310	Flat Black Curved Stack
1610	Standard Fuel Filter with Water Separator and Standard Fuel Fill
9015	Engine Block Heater
9240	Engine Compartment Light

1217	140 amp Alternator
2730	30 Amp Converter
7140	Premium LED Work and Drive Lights All exterior machine lights are LED LED Front Turn/Marker & Rear Turn/Brake Lights
1120	5-Speed Powershift Transmission with Lock-up Torque Converter Recommend Ride Control with Lock-up Torque Converter for Load and Carry applications.
3046	Front Hydraulically Locking Differential and Rear Conventional Differential Axles
3110	Automatic Differential Lock Allows operator to switch on Automatic Diff Lock providing continual differential lock in all conditions, minimizing tire spin.
2010	Standard Z-BAR
2360	Joystick Controls Provides a single lever (joystick) control for the boom and the bucket. Optional 3rd and 4th functions are controlled with proportional thumb rollers integrated in the joystick handle. Includes FNR switch integrated into the joystick control lever.
2403	Three Function Hydraulics Controls Boom and Bucket and adds an auxiliary function and boom lines.
1970	Hydrau Hydraulic Fluid
2515	Ride Control
1910	Premium Cab
8450	Cab with Air A/C Charge
2240	Premium Seat, Heated and Ventilated with Heavy Duty Air Suspension
1945	7 inch Monitor with Dedicated Rear Camera Display Provides a separate and dedicated 7 inch display monitor for displaying continuous rear view camera imagery and allowing standard monitor to display without interruption.
8350	Remote Powered and Heated Exterior Mirrors
8370	Premium AM/FM/Weather Band (WB) with Bluetooth, Remote Aux and Remote USB Port
8235	Rear Camera and Rear Object Radar Detection Display shows view behind the machine and provides audible alert. Rear view is displayed in video-enabled color monitor or dedicated color monitor.
8298	No Strobe Beacon or Left Beacon Bracket
5610	Left Side Steps Only

9140	Fire Extinguisher 5.0 lbs. multi purpose (ABC) Dry Chemical Fire Extinguisher mounted inside the cab to the left front ROPS post.
2120	Steering Wheel Only
2890	No Payload Scale without Cycle Counter
170K	JDLink™

Includes integrated cab wiring harness, antenna, and JDLink™ Modem (MTG).

JDLink™ connectivity is enabled separately through the JDLink™ website.
Connectivity service is subject to country availability.

5550	Full Width Front and Rear Fenders Includes full width front and rear fenders, left side steps, as well as both left and right side platforms.
-------------	---

Fender width is wider than tire by design to capture more tire spray but is susceptible to damage if tire brushes against objects from the side.

4415	Michelin, 20.5R25 L2 Radial Tires with 3pc Rims
8560	Hydraulic Coupler - JRB 416 Pattern
8915	3.25 Cu. Yd. Bucket (Coupler only) All 3.25 cu yd buckets are 106" (2692 mm) wide Enhanced Production buckets with weld-on Skid Shoes and integrated spill guard.

8860	Bolt-on Cutting Edge
-------------	-----------------------------

5760	60 in (1524mm) Wide Fork Frame
-------------	---------------------------------------

5870	60 Inch (1524mm) Construction Tines
-------------	--

8220	Rear Hitch and Counterweight
9210	Electrical Corrosion Prevention Package Preventive corrosion treatment for use in corrosive environments. Preventive corrosion treatment includes dielectric grease for electrical connections and polyurethane-based sealant on exposed terminals.

9410	Transmission and Bottom Guards Recommended in applications where underside is vulnerable. Includes transmission side guards, bottom guards, and loader mast side covers.
-------------	---

9520	License Plate Bracket Includes light for night time illumination.
-------------	---

PA state contract number 440019965	
One year comprehensive warranty	Included
Five year 3000 hour emissions warranty	Included
Additional three year or 2000 hour extended powertrain & hydraulic warranty	Included
Rockland 3.5YD. Half side grapple bucket	Included
Less trade value of Deere 544K	(\$45,000.00)
PA state contract sale price	\$199,900.00
Quote is valid for the current calendar month	