

Village of Greenville

Erosion Control Permit Requirements

Summary of Erosion Control Requirements

- 1) A stone tracking pad must be installed prior to any ground disturbance on the site (excluding grading of driveway subgrade). The tracking pad shall be placed with 3”– 6” clear crushed stone, installed for the full width of the proposed egress point, a minimum of 12” thickness, and shall extend the length of the driveway from the roadway to foundation or a maximum of 50 feet. The tracking pad shall be maintained until permanent ground cover has been established or a permanent driveway surface has been installed.
- 2) All traffic, including construction equipment and delivery vehicles, must enter and exit the site using the stone tracking pad. No alternative access points will be allowed.
- 3) Perimeter erosion control measures must be in place before any land disturbance on the site. Erosion control shall be placed along downslope areas and other sloped areas as required to prevent or reduce erosion.
- 4) All effected public storm sewer inlets shall be protected with erosion control measures.
- 5) All building materials waste shall be properly managed and disposed of to prevent pollutants and debris from being carried off the site by runoff.
- 6) All dumpsters must be placed on a hardened surface and access to dumpster must be provided without tracking sediment onto the roadway.
- 7) Certificate of Permit Coverage must be placed in a conspicuous place at the construction site.
- 8) Greenville Public Works Department shall be notified 48 hours prior to any land disturbance.
- 9) Erosion control materials shall be “PAL” certified. See WisDOT website link below for details:

<https://wisconsindot.gov/Pages/doing-bus/eng-consultants/cnslt-rsrcs/tools/pal/default.aspx>

Maintenance of Erosion Control Practices

- 1) All erosion control practices must be inspected weekly or 24 hours after a rainfall event of 0.5 inches or greater. The erosion control permit holder shall inspect and maintain erosion control measures in working condition. Erosion control inspection log shall be kept on site or in an easily accessible location.
- 2) Greenville may conduct periodic erosion control inspections throughout the duration of the project. If violations are found, the applicant will receive a written notice and will have 48 hours for corrective action. If the violation is not corrected in 48 hours, a stop work order or fine may be issued.
- 3) Accumulated sediment will be removed from behind sediment fences and barriers before it reaches a depth that is equal to half the barrier height.
- 4) Breaks and gaps in sediment fences and barriers will be repaired immediately. Decomposing straw bales will be replaced (typical bale life is 3 months).
- 5) Any sediment tracked onto the roadway shall be cleaned up by the end of the same workday.
- 6) All erosion control practices will be maintained until the disturbed areas they protect are permanently stabilized and established. Upon establishment of permanent stabilization, the temporary erosion control practices shall be removed.