



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG





## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG





## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG





## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG





## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG





## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG





## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG





## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG



## ST. TAMMANY PARISH

MICHAEL B. COOPER  
PARISH PRESIDENT

### RESIDENTIAL ROOFING PERMIT

- Completed Permit Application
- Signed Contract Showing Roof Specs & Total Project Cost

Permit Number \_\_\_\_\_ Date \_\_\_\_\_  
Company Name \_\_\_\_\_  
Phone Number \_\_\_\_\_ Email \_\_\_\_\_  
Customer Name \_\_\_\_\_  
Jobsite Address \_\_\_\_\_

- Shingles classification shall be either ASTM D7158 (G or H) or ASTM D3161 (F)
- Shingles will be rated for 140 MPH ultimate wind speed.
- Underlayment shall be two layers applied in the following manner: apply a 19-inch strip of underlayment felt parallel to and starting at the eaves. Starting at the eave, apply 36-inch-wide sheets of underlayment, overlapping successive sheets 19 inches. Distortions in the underlayment shall not interfere with the ability of the shingles to seal. End laps shall be 4 inches and shall be offset by 6 feet.
- Roofs installed to Fortified Standards shall require certificate upon completion.
- Asphalt shingles will be fastened to solidly sheathed decking.
- A drip edge will be provided at eaves and rake edges and shall be overlapped not less than 2 inches.
- Photos with geotagging are required for new roofs and roof replacement, photos need to show, Decking, Underlayment, Lapping, Nailing, Taping, Flashing, Drip Edge, Crickets, and photo of all sides of roof when complete.
- Any existing flashing, edging, outlets, and vents that are rusted, damaged, or deteriorated will be replaced.
- Roof will be done in compliance with Chapter 9 Of the 2021 International Residential Code.

I, the contractor, have read and examined all of the requirements listed above and understand that it is my responsibility, and the responsibility of all persons contracted by me, to adhere to these guidelines.

Signature \_\_\_\_\_ Date \_\_\_\_\_

**Remodel: \$100.00 plus \$5.00 per \$1,000.00 of executed contract amount.**

[NAME] , [TITLE] | [DEPARTMENT]

P.O. BOX 628 | COVINGTON, LOUISIANA | 70434 | [EMAIL]@STPGOV.ORG | 985-898-3427  
WWW.STPGOV.ORG