4A. There is one existing formhouse along with several out buildings and an inground pool located within the subject property.

4H. There is no flood plain on the site.

All utilities in the Township have been contacted.

. The developer shall comply with all applicable Upper Allen Township Ordinances in effect at the ime of submission of the Preliminary Plan. 10. The developer shall be responsible for the placement of all street name and traffic control signs that a name signs and traffic control signs shall be installed per the Upper Allen Township's Zoning Post Critics Treat names and addresses shall be approved by the Township and the United States Post Office.

13. Lot 44 shall be owned and maintained by Upper Allen Township for the Township Walking

15. Lots 41, 43, and 45 shall be owned and maintained by the Pennington Homeow Association and remain undeveloped as required by the Upper Allen Township Ordina

16D. Water main and appurtenance to be designed and installed by United Water Company of

17A. Upon completion of the sanitary sewer, the Contractor shall provide "As Built" drawings to the developer's engineer for preparation of "Record Drawings" drawings. Two record sets of "Record Drawings" drawings as completed by the Engineer shall be provided to the Upper Allen Township staff. Red line markup drawings are not acceptable.

178. All sanitory sewer construction methods and materials shall conform to the latest standards of Upper Allen Township, Cumberland County, Pennsylvonic, and shall be subject to the approval by the township engineer. The contractor should refer to the detail in the Standard Construction and Material Specifications of Upper Allen Township. 18. The site is in the presence of subsurface limestone in the Epler, Martinsburg and Myerstown

21. The existing dwelling on Lot 39 is non-conforming relative to the proposed dedicated ultimate right—of-way line for Mount Allen Drive and the current required setback line. Use may continue in accordance with the Upper Allen Township Zoning Ordinance Chapter 245. Article XXII, "Nonconforming Lots, Uses and Buildings". If the dwelling is wholly or partially destroyed by fire, explosion, flood or other phenomenon or legally condemned, the dwelling not be reconstructed with the start of reconstruction beginning within one year in accordance with Article XXII.

mercus, we concurred ultimate right-of-way line required by the Township of Upper Allen encroaches upon and/or passes through the dwelling house rected on Lot 3/8 as shown on the Preliminary Subdivision Plan, Jim Jum, LLP reserves the right that just compensation be paid as provided by the eminent domain code to the Owner/s of solid structure, at such times to the contract of the

REVISED FINAL - PHASE ONE & TWO SUBDIVISION

AND LAND DEVELOPMENT PLAN

PENNINGTON MOUNT ALLEN DRIVE **UPPER ALLEN TOWNSHIP** CUMBERLAND COUNTY, PENNSYLVANIA

2403 NORTH FRONT STREET

2403 NORTH FRONT STREET
HARRISBURG, PA 17110
PHONE: (717) 233-1026
FAX: (717) 233-2192
CONTACT: EUZABETH C. DAMSON, P.E.
EMAIL: BETSY.DAVISON@HEBLACK.COM

OVERALL EXIST. COND. PLAN EXISTING CONDITIONS PLAN EXISTING CONDITIONS PLAN

EXISTING CONDITIONS PLAN

PHASING PLAN
OVERALL SUBDIVISION PLAN
SUBDIVISION PLAN

OVERALL EROSION CONTROL PLAN EROSION CONTROL PLAN EROSION CONTROL PLAN

SUBDIVISION PLAN DESCRIPTIONS
OVERALL GRADING PLAN

OF 36 GRADING/UTILITY PLAN
OF 36 GRADING/UTILITY PLAN
OF 36 FORCEMAIN CONNECTION
OF 36 PUMPSTATION LAYOUT
B OF 36 LANDSCAPE PLAN
9 OF 36 PENNINGTON DRIVE
20 OF 36 PENNINGTON DRIVE
21 OF 36 PENNINGTON DRIVE
22 OF 36 PROFILES
23 OF 36 PROFILES
24 OF 36 PROFILES
25 OF 36 PROFILES - FORCEMAIN CON'
26 OF 36 PROFILES - FORCEMAIN CON'
27 OF 36 PROFILES - FORCEMAIN CON'
28 OF 36 PROFILES - FORCEMAIN CON'
29 OF 36 EROSION CONTROL PLAN
29 OF 36 EROSION CONTROL PLAN
30 OF 36 EROSION CONTROL PLAN
31 OF 36 EROSION CONTROL DETAIL'
31 OF 36 EROSION CONTROL DETAIL'
32 OF 36 EROSION CONTROL DETAIL'
33 OF 36 DETAILS
34 OF 36 DETAILS
35 OF 36 DETAILS
4 * 36 OF 36 LANDSCAPE DETAILS

* PLANS PREVIOUSLY RECORDED 8-18

* PLANS PREVIOUSLY RECORDED 8-18-08
** PLANS INCLUDED IN REVISED FINAL PHASE
ONE & TWO SUBDIVISION RECORDED 12-17-10.

CONDITIONAL USE APPROVAL - November 17, 2010

The Board of Commissioners approved the Conditional Use request for Special asion Harne use on lot 39 and parking in the Greenway Area by Suites at Stock:

The Board of Commissioners voted to accept construction of the walking trail in of the recreation fee.

DEFERMENT NOTE - July 2, 2008

PLANS INCLUDED IN REVISED FINAL PHASE ONE & TWO SUBDIVISION TO BE RECORDED.

GRADING/UTILITY PLAN
GRADING/UTILITY PLAN

SHEET INDEX



LOCATIONS OF EXISTING UNDERGROUND UTILITIES ARE BASED UPON SURFACE FUDENCE AND EXISTING DRAWING AND ARE NOT GUARANTEED TO BE COMPLETE OR ACCURATE BY HEDWARD BLAND ASSOC, P.C. CONTRACTORS TO CONTACT PA. ONE CALL SYSTEMS, INC. (1-800-242-1776) T ESTABUSH EXISTING UTILITY LOCATIONS AT LEAST THREE(3). WORKING ANY SAFENGY TO THE START OF ANY EARTHMOUND

PA ONE CALL DESIGN NUMBER: 20110110389

UTILITY LIST

VERIZON STRAWBERRY SQUARE, FLOOR 11 HARRISBURG, PA 17101-4887 (717) 777-4887

COMCAST CABLE TV CO., INC 4601 SMITH STREET HARRISBURG, PA 17109 (717) 651-1915

UGI UTILITIES, INC. 1500 PAXTON STREET HARRISBURG, PA 17105-3565 (717) 234-5951 UNITED WATER PENNSYLVANIA 4211 EAST PARK CIRCLE HARRISBURG, PA 17111-0151 (717) 561-1103

PLAN PURPOSE

DIL	ASING			
PH	ASING.	SCH	-1311	1 F

PHASE	YEAR		OPEN SPACE (ocres)	% TOTAL AREA	NO. BUILDING LOTS	% TOTAL UNITS	LENGTH STREETS	LENGTH STORM SEWERS
1	2007-2020	16.289	31.01	85.71	27	69.2%	3391'±	2222°±
2	2007-2020	4.737	3.15	14.29	12	30.8%	0	1820'±
TOTAL		21.026	34.16	100.00	39	100.00	3391'±	4042'±

ZONING/SITE DATA - PHASE ONE & TWO

RL RURAL LIVING DISTRICT - OPTION 2 CSO CONSERVATION DESIGN OVERLAY DISTRICT

SSP STEEP SLOPE PROT	ECTION DISTRICT
	PROVIDED
	38 SINGLE FAMILY DWELLING 1 EXISTING FARM HOUSE TO
TOTAL SITE AREA TOTAL DEVELOPABLE AREA	55,186 ACRES 21,026 ACRES
ORIGINAL -TOTAL GREEN AREA/OPEN SPACE CALCULATION	34.16 ACRES (61.9%) 2.63 AC + (52.556 AC * 60
REVISED - TOTAL GREEN AREA/OPEN SPACE CALCULATION	34.16 AC - 1.47 AC = 32.6 32.69 AC - 2.63 AC = 30.
TOTAL CONSTRAINED LANDS (INCLUDED IN OPEN SPACE)	2.63 ACRES
MAXIMUM DENSITY	60,000 S.F./D.U.

39 DWELLING UNITS 0.71 D.U. /AC. 17,000 S.F. MAXIMUM IMPERVIOUS AREA 30% PER LOT (NOT TO EXCEED) AXIMUM BUILDING HEIGH

OPEN SPACE

YPICAL LOT AREA

JILDING SETBACKS MINIMUM FRONT YARD MINIMUM SIDE YARD

MINIMUM REAR YARD PROPOSED SEWAGE DISPOSAL PROPOSED WATER SUPPLY NEW STREETS

Open Space Lot 40 shall be awned and maintained as Greenway area in accordance with the Upper Allen Township Zoning Ordinance. Lot 40 shall also be owned and maintained as deed restricted Open Space by the Owner of Lot 39.

39 Year Open Space Spa

WAIVER APPROVED - November 7, 2007

Waiver from mapping the existing wetlands and large trees over 30° in diameter. 20-9.C.(2)(s)

DEFERMENTS APPROVED - Nov. 7, 2007

Deferment for additional plantings in Type II Buffer Yard along Mt. Allen Drive. 0-26.B(1))

Deferment of street widening and installing curbs and sidewalks along Mount Alien e. (220-15.B(11)(a), (220-16.A(2), (220-16.B(3))(Deleted by deferment July 2, 2008)

H. EDWARD BLACK and ASSOCIATES, LTD.

This subdivision shall be know and designated as <u>Pennington</u>. A streets, alleys, and public walking trail shown and not heretofore dedicated are hereby dedicated to the public.

There are strips of ground thirty (30') feet in width as shown of

The foregoing covenants (or restrictions) are to run with the land and shall be binding an all parties and all persons claiming under them until Jounnary 1, 2033, at which time sold covenants or restrictions) shall be automatically extended for successive periods of 10 years and shall remain in full force and effect unless changed at the end of such period of 10 years by vote of a majority of the then owners of the building sites covered by these covenants (or restrictions).

The right to enforce these provisions by injunction, together with the right to cause the removal, by due process of law, of ony structure or port thereof exceted or maintained in violation hereof, is hereby dedicated to the public and reserved to the several owners of the several objects of the several objects.

Witness our Hands and Seals this_____day of___

____ 20___ before me, the

There are strips of ground thirty (30) feet in width as shown on this plan and marked: "Easement, reserved for the use of public utilities for the installation of rotate as were mains, poles, ducts, lines and wires, subject of all timesers may be used to the control of the co

The right to enforce these provisions by injunction, together with the right to couse the removel, by due process of law, of any structure or port thereof erected or maintained in violation hereof, is hereby dedicated to the public and reserved to the several owners of the several lots in this subdivision and to their hairs and assigns.

Witness our Hands and Seals this _____ day of _____, 20__

On this, the day of 20, before me, ti undersigned officer, personally come known to me for satisfactorily proven) to be the person whose name is subscribed to the within instrument, and acknowledged that express therein contained.

Commonwealth of Pennsylvania:

On this, the _____day of ______20___, before me, ti undersigned officer, personally come ______known to me (or satisfactorily proven) to be the person whose name is subscribed to the within instrument, and acknowledged that _______executed the same for the purposes therein contained.

IN MTNESS WHEREOF, I have hereunto set my hand and official

My commission expires:

We, <u>Austin & Down Howell</u>, the undersigned, owners of the owners of lot 21 shown and described herein, do hereby certify that we have laid off, platted and subdivided, and hereby lay off, plan and subdivide, said real estate in accordance with the within plan.

The foregoing covenants (or restrictions) are to run with the land and shall be binding on all parties and all persons claiming under them until abonary 1, 2033, at which time sold covenants (or restrictions) shall be automatically extended for successive periods of 10 years and shall remain in full force and effect unless changed at the end of such period of 10 years by vote of a majority of the then owners of the building sites covered by these covenants (or restrictions).

Commonwealth of Pennsylvania:

IN WITNESS WHEREOF, I have hereunto set my hand and official seal.

JIM JAM LLC 6 LYNCHBURG COURT MECHANICSBURG PA 17050 INSTRUMENT # 200828177 CONTACT: JAMES W. MUMPER PHONE: 717 691 6919 42-11-0274-073 21 42-11-0274-92 INSTRUMENT # 201204398 MECHANICSBURG, PA 1705 6 LYNCHBURG COURT MECHANICSBURG PA 17050 CONTACT: JAMES W. MUMPER 42-11-0274-091 DEED BOOK 200832198 PHONE: 717.691.6919
NER: SUITES AT STOCKS, INC
16 STONE SPRING LANE CAMP HILL PA 17011 CONTACT. STEPHEN WEINSTOCK

OWNER/DEVELOPER TAX PARCEL

We, <u>Jim Jam. LLC.</u> the undersigned, owners of the real estate shown and described herein, do hereby certify that we have laid off, platted and subdivided, and hereby lay off, plan and subdivide, said real estate in accordance with the within plan.

There are strips of ground thirty. (30) feet in width as shown on this plan and marked: "Easement, reserved for the use of public utilities for the installation of water and saver mains, post ducts, lines and wires, subject at all times to the proper ducts, lines and to the cosement herein reserved. No buildings or other structures are to be erected or maintained upon said strips of land, but owners of lots in this subdivision shall take their titles subject to the rights of the utilities.

The foregoing covenants (or restrictions) are to run with the land and shall be binding on all parties and all persons claiming under them until January 1, 2033, at which time solid covenants (or restrictions) shall be automatically extended for successive periods of 10 years and shall remain in full force and effect periods of 10 years and shall remain in full force and effect or majority of that he end of sour period of 10 years by vote of a majority of the state of source in the building sites covered by these covenants (or restrictions).

The right to enforce these provisions by injunction, together with the right to cause the remove), by due process of law, of any structure or port thereof exceled or maintained to the hereof, is hereby dedicated to the public and reserved to the several owners of the several losts in this subdivision and to their sand casigns.

Witness our Hands and Seals this_____day of______, 20___ Commonwealth of Pennsylvania:

County of Cumberland:

IN WITNESS WHEREOF, I have hereunto set my hand and official

(§214-22.B.(24)).

OWNER (AUSTIN HOWELL) I HEREBY ACKNOWLEDGE THAT THE STORMWATER MANAGEMENT FACILITIES AND BMPS ARE TO BE PERMANENT FIXTURES THAT CAN BE ALTERED OR REMOVED ONLY AFTER APPROVAL OF A REVISED PLAN BY THE MUNICIPALITY.

EDUTABLE OWNER (STEPHEN R MEHISTOCK) EQUITABLE OWNER (KATHY J. MEHISTO I HEREBY ACKNOWLEDGE THAT THE STORMWATER MANAGEMENT FACILITIES AND BMPS ARE TO BE PERMANENT FIXTURES THAT CAN BE ALTERED OR REMOVED ONLY AFTER APPROVAL OF A REVISED PLAN BY THE MUNICIPALITY.

JW MUMPER CONSTRUCTION

INSTRUMENT No. _____
COMMONWEALTH OF PENNSYLVANIA

COUNTY OF CUMBERLAND
ON THE ____ DAY OF ____, 20 ___. THE
UNDERSIGNED INDIVIDUAL PERSONALLY APPEARED
BEFORE ME, BEING

WHO DULY SWORN ACCORDING TO LAW, DEPOSE AND SAY THAT THEY ARE THE OWNERS OF THE PROPERTY SHOWN ON THIS PLAN AND THAT THEY ACKNOWLEDGE THE SAME TO BE RECORDED AS SUCH ACCORDING TO LAW.

WITNESS MY HAND AND NOTORIAL SEAL THE DAY AND DATE ABOVE WRITTEN.

NOTARY PUBLIC (NOTARIAL SEAL)
COMMONWEALTH OF PENNSYLVANIA COMMONWEALTH OF PENNSYLVANIA
COUNTY OF CUMBERLAND
ON THE DAY OF 20 THE
UNDERSIGNED INDIVIDUAL PERSONALLY APPEARED
BEFORE ME, BEING

CHINER (AUSTIN HOME) () OWNER (ASTRI HOREL)
WHO DILLY SWORN ACCORDING TO LAW, DEPOSE AND SAY THAT THEY ARE THE OWNERS OF THE PROPERTY SHOWN ON THIS PLAN AND THAT THEY ACKNOWLEDGE THE SAME TO BE RECORDED AS SUCH ACCORDING TO LAW.

WITNESS MY HAND AND NOTORIAL SEAL THE DAY AND DATE ABOVE WRITTEN.

COMMONWEALTH OF PENNSYLVANIA

OWNER (STEVEN R. WEINSTOCK)

OWER RAWY & MEMOTION)
WHO DULY SWORN ACCORDING TO LAW, DEPOSE AND
SAY THAT THEY ARE THE OWNERS OF THE
PROPERTY SHOWN ON THIS PLAN AND THAT THEY
ACKNOWLEDGE THE SAME TO BE RECORDED AS SUCH
ACCORDING TO LAW.

WITNESS MY HAND AND NOTORIAL SEAL THE DAY AND DATE ABOVE WRITTEN.

SEORETARY.

SURVEYORS CERIFICATE
I, GREGORY L. CONDON, PLS, HEREBY CERTIFY THAT
I AM A REGISTERED LAND SURVEYOR IN COMPLIANCE
PENNSTLVANA, THAT THIS PLAN CORRECTLY
REPRESENTS A SURVEY COMPLETED BY ME ON
ACTUALLY EXIST. AND THAT THIS LOCATION, SIZE
THE AND MALERIAL ARE ACCURACLY SONOM.

GREGORY L. CONDON, PLS BISCON LAND SURVEYING CO. 50 MAPLEWOOD DR., SUITE A

ETTERS, PA 17319


DATE SEAL ENGINEER/LANDSCAPE ARCHITECT'S CERTIFICATE I HEREBY CERTIFY THAT I HAVE DESIGNED ALL SITE AND PUBLIC IMPROVEMENTS AND HAVE IDENTIFIED ALL FLOOD PLAN LIMITS AS REQUIRED FOR THIS SUBDIVISION.


ELIZABETH C. DAYSON, P.E.


MARE

H. EDWARD BLACK & ASSOC. 2403 NORTH FRONT STREET


HARRISBURG, PA 17110 OF 16 FOR RECORDING Sheet 1 OF























CENTER LINE CURVE TABLE								
CURVE	LENGTH	RADIUS	DELTA	TANGENT	CHORD	CHORD DIR.		
C300	226.12	500.00	25"54"40"	115.03	224.20	N59"18'20"E		
C301	133.09	300.00	25"25'09"	67.66	132.01	N33'38'26"E		
C302	157.35	150.00	60'06'12"	86.78	150.23	S50*58'57"W		
C303	616.03	250.00	141"11'04"	709.60	471.59	N10"26"32"E		
C304	76.53	150.00	2973'53"	39.12	75.70	N74'45'56"W		
C305	49.03	150.00	18'43'37"	24.73	48.81	S8175'19"W		
C306	65.81	150.00	25"08"14"	33.44	65.28	N84"27"37"E		
C307	84.38	150.00	3273'44"	43.34	83.27	S80*54*52*W		

	TER LINELINE	
LINE	LENGTH	BEARING
L300	318.75	N7275'40"E
L301	128.57	N46"21"00"E
L302	280.36	N20"55'51"E
L303	176.60	N60"09'00"W
L304	147.36	N89"22"53"W
L305	576.20	S71"53"30"W
L306	71.79	N82'58'16"W
L307	283.21	564'48'00"W

		EAS	EMENT CURY	VE TABLE		
CURVE	LENGTH	RADIUS	DELTA	TANGENT	CHORD	CHORD DIR.
EC1	72.04	54.57	75"38"06"	42.36	66.92	N13"57"07"W
EC2	77.94	95.12	46"56"54"	41.31	75.78	N47"20"24"E
EC3	267.86	325.00	47"3"18"	142.06	260.34	S44'32'30"W
EC4	32.44	24.57	75"38'06"	19.07	30.13	N13"57"07"W
EC5	52.83	65.12	46"29"02"	27.97	51.40	N47"06"28"E
EC6	292.85	355.00	4775'54"	155.34	284.62	S44'33'48"W
EC7	11.85	175.00	3'52'43"	5.93	11.84	N73'49'51"E
EC8	12.04	125.00	5'31'08"	6.02	12.04	N74"39"04"E
EC9	34.01	275.00	7'05'12"	17.03	33.99	N74"23"44"E
EC10	15.01	275.00	3"07'36"	7.51	15.01	N21'38'30"E
EC11	15.01	275.00	3'07'36"	7.51	15.01	N18'30'53"E
EC12	127.68	125.00	58'31'26"	70.04	122.20	N12"25'02"E
EC401	2.08	56.00	2"07"49"	1.04	2.08	S18"54'46"E
EC402	45.23	44.00	58*53'37*	24.84	43.26	N4717'40"W
FOAGT	4 07	44.00	A Mi. A	0.40	4.07	

MANHOLE	NORTHINGS	AND EASTINGS
ANHOLE #	NORTHING	EASTING
MH-PF1	6853.0413	12640.3492
MH-PF2	6945.1878	12914.9248
MH-PF3	7136.7337	13152.7349
MH-PF4	7508.7577	13319.5687
MH-PF5	7570.3863	13375.0252
MH-PF6	7593.6212	13443.6309
MH-PF7	7441.9540	13591.8208
MH-PF8	7727.7676	13891.4306
MH-PF9	7908.3170	14248.3647
MH-PF10	7665.4110	13572.7420
MH-PF11	7815.5892	13641.0903
MH-PF12	7984.3988	13594.9563
MH-PF13	8145.0972	13359.5821
MH-PF14	8164.1762	13170.5425
MH-PF15	8097.9337	12913.9554
MH-PF16	8028.4846	12701.5801
MH-PF17	8249.9442	12629.1602
MH-PF18	7972.7146	12525.9544
MH-PF19	7979.8785	12370.0168
MH-PF20	7934.4989	12258.9281

E	1 243.46	\$17*44'20"F
E:	41.68	N72'40'30"F
E.	32.43	\$17*44'20"E N72*40'30"E \$34*07'45"E
E4	117.25	
ES ES	80.66	N17'44'20"W
E	138.20	N7275'40"E
E	81.11	N62"21"24"E
E8	33.04	N30°20'26"W
ES	76.70	S62"21'24"W
E10		S62'21'24"W S72'15'11"W N17'44'20"W S69'04'09"E
E1	90.17 159.45 30.00	N17*44*20*W
E12	150.17	
	30.00	S00"12"38"W S89"47"22"E
E14	180.17	
E16	180.17	N0012'38"E
E17	10.90	N69'04'09'W
£18		529 51 UU W
F19		S61'46'10"E
F20	34.18 70.43	N0012'38'E N6974'09'W \$29'51'00'W \$03'03'15'E \$51'46'10'E \$68'09'09'W \$20'55'51'W \$16'48'24'E \$69'04'09'E \$29'51'00'W \$03'03'15'E \$51'46'10'E \$6811'46'W
F2:	60.57	\$20°55'51"W
E22	60.57 56.18	S16'48'24"F
E20 E22 E23	115.62	S69"04'09"F
E24	112.29	\$29"51"00"W
E25	83.14	S03'03'15"F
E26	47.77	S51'46'10"E
E25 E26 E27	83.14 47.77 72.08	S6871'46"W
E28 E29	174.42	S20"55"51"W
E29	30.00	S69°04'09°E
E30	50.49	N59"35"23"E
E30 E31	118.46	S51'46'10"E S68'11'46"W S20'55'51"W S69'04'09"E N59'35'23"E S69'04'09"E
E32	142.09 75.05	S69"55'19"E
E33	75.05	S11"53'57"E
E34		S69'55'19"E S11'53'57"E S50'44'23"W
E35	79.04	S35 03 00 W
	190.36	\$44*53'10*W \$43*39'00*E
E37	106.92 158.73	S43*39'00*E
E38	158.73	S69*55*19*E
E39	80.37 30.94	S11*53'57*E N58'35'44*E
E40	30.94	N58'35'44"E
E41	361.07 145.39 140.67	
E42 E43	140.67	N32'33'22"W N52'25'19"W N60'09'00"W
	113.00	N52 25 19 W
E44	113.99 135.00 32.52 172.59	N60°09'00"W S29"51'00"W
E45 E46	32.52	529 51 00 W
E47	172 59	S71°53'30"W S83°58'03"W
E48	203.49	564"07"05"W
E49	203.49 35.00 30.00	\$8358'03" W \$18'06'30" E \$71'53'30" W N8'06'50" W N6'407'05" E N8358'03" E \$88'26'23" E \$69'03'37" E N6'58'38" E \$83'30'122" E \$332'14'15" E \$60'00" 60" E
F50	30.00	\$7153'30"W
E51	65.62	N18'06'30"W
E52	202.10	N64"07"05"F
E52 E53	179.83	N83*58'03"E
E61	153.81	S88*26'23*E
E62 E63	118.23 12.21	S69'03'37"E
E63	12.21	N06"58'38"E
E64		S83'01'22"E
E65	16.00	\$3274'15"E
E69 E70 E71	106.09 147.95	S60°09'00°E S52°25'19°E S32°33'22°E
E70	147.95	S52"25"19"E
E71	156.04	S32'33'22"E
E72 E73	365.95	S1270'10"E
E73	49.61	\$1270'10"E N77'04'03"E
E74	37.80 38.42 170.34 343.25	S75'46'22"E
E75 E76	38.42	
6/0	170.34	500'37'07"W
E77	343.25	\$71°55'45"W
E78 E79	33.79	N18'06'30"W
E80	33.79 323.10 144.59	\$43.39.00 E \$00'37'07"W \$71'55'45"W N18'06'30"W N71'53'30"E N00'37'07"E \$88'26'23"E
E82	146.69	N00'37'07'E
E82 E83	134.95	S69 03'37"E
E84	132.47	
E85	146.15	
F86	7 11	\$76°22'46°C
E86 E87	7.11 49.47	576"22'46"E N72"00'30"E S27"17'53"W
E88	106.58	\$27"17"53"W
E89	5 60	N38-38,00_M
E90	56.25	N25"55"15"W
E91	164.25	A14 040 774 7744
E92 E93	124.56 135.38	N18'07'12"W S82'29'01"W S71'53'30"W N18'06'30"W N71'53'34"E N82'29'01"E S1972'12"E
E93	135.38	S82"29"01"W
E94	99.71	S71"53"30"W
E95	30.00	N18'06'30"W
E96	102.50	N71"53'34"E
E97	162.61	N82"29'01"E
E98	150.13	
E99	210.00	N18*06*30*W
E100	30.00	N71'53'30"E S18'06'30"E S43'39'00"E N46'21'00"E N63'10'05"E
E101	210.00	\$18*06'30"E
E102 E103	159.36	543'39'00'E
E103	401.29 264.74 260.31	N46"21"00"E
E104 E105	264.74	3 CO UF COM
FIDE	426.85	S63"10"05"W
E106	205.34	S63"10'05"W S46"21'00"W N43'39'00"W
F111	15.00	
E112	15.00 3.16	571'53'30 W
E111 E112 E113	17.99	571 53 30 W
E114	30.00	N71"53"30"F
£115	15.00	S89"22"53"F
E116	15.00	S89"22"53"F
F117	14.99	\$71'53'30 W \$71'53'30"W \$71'53'30"E \$89'22'53"E \$89'22'53"E \$89'22'53"E \$20'55'51"E
E118	15.01	N20'55'51"E
E1191	15.00	N20"55"51"E
E120 E121	15.00	N20"55"51"E N20"55"51"E N20"55"51"E S72"15"40"W
E121	15.00	S72"15"40"W
	30.00	S72"15'40"W
E123	31.68	\$72"15'40"W N72'40'30"E
E124	72.81	S01*24'06"W
E125	95.39 30.00	N01*24'06"E
E126	30.00	\$46"21"00"W
	30.00	S43'39'00'E
E128 E129 E130	17.59 15.00	S46"21'00"W
£129	15.00	\$60°09'00"E
EIJU	15.00	S60*09'00*E

LINE	LENGTH	BEARING
LI	141.65	\$46"21"00" V
L2	165.07	
L3	162.72	\$32*51*47*W \$09*02*29*W
L4	150.71	\$32'33'22"[
L5	146.29	S52'31'38"E
L6	163.11	N83'58'03"E
L7	120.00	N71*53'30"E
L8	135.00	N71*53'30"E
L9	164.76	S43'39'00"E
L10	155.00	N18*06'30"W
L11	155.00	N18'06'30"W
L12	155.00	N18*06'30"W
L13	150.25	\$88*26'23"E
L14	150.00	S00'37'07"W
L15	50.00	S18'06'30"E
L16	155.04	S69°03'37°E
L17	150.00	N07'41'11"E
L18	128.00	N60"09'00"W
L19	150.00	N4773'51"E
L20	150.00	N29"51'00"E
L21	150.00	N29"51"00"E
L22	150.14	N1270'10"W
L23	150.00	N67"39"25"E
L24	150.00	N88'00'16"E
L25	150.00	\$69*55'19*E
L26	150.00	N18'06'30"W
L27	157.51	N18'06'30"W
L27 L28	156.53	N18'06'30"W
L29	113.78	N18'06'30"W
L30	160.00	N18*06'30"W
L31	160.00	
L32	150.00	N18'06'30"W
133	150.00	N18'06'30"W
L34	150.00	N18'06'30"W
L35	150.00	N18'06'30"W
L36	149.88	N00"37"07"E
L37	150.59	N17"29'00"E
L38	150.00	N29"51"00"E
L39	150.00	N52"57"15"E
L40	150.00	S78*06'27*E
L41	150.00	\$18*52'43"F
L42	78.12	N21'43'30"W
L43	148.34	N21*42'30"W
L44	145.35	N6817'30"E
L45	150.00	N35"51'58"W
L46	93.46	S39'58'37"W
L47	120.00	N20"55"51"E
L48	130.00	N20"55"51"E
L49	150.00	N66"26'59"W
L50	150.00	N69"04'09"W
L51	150.00	N69"04'09"W
L53	169.02	S2813'47"W
L54	13.73 100.72	S20"55"51"W N69"07'29"W
L55	100.72	N69'07'29"W
L56	150.00	N69"04"09"W
L57	153.42	S50'30'18"E
L58	150.00	\$43'39'00"E
L59		N62"21'24"E
L60	156.53	S35'42'41"E
L61	150.00	N17'44'20"W N17'44'20"W
		N17'44'20"W
L63	152.42	N22'35'11"W
L64	132.88	N72"15'40"E
		N7215'40"E
L66	71.45 137.05	S64*48'00"W
L67	33.22	S64'48'00"W
	71.79	S64'48'00"W
L69	/1./9	N82"58'16"W
L70	147.55	S71*53'30"W
	153.65	S71*53'30"W
L72	135.00	S71*53'30"W
L73	120.00	\$71"53'30"W \$71"53'30"W
	37.12	S71"53'30"W N89"22'53"W
L75		

LINE	LINE TA	BEARING
L7	110.24	N89°22'53"W
L7!	30.56	N89*22'53"W N60*09'00"W
L80		
L8	1 120.01	N20"55"51"E
L82	145.01	N20"55"51"F
L83		N20'55'51"E N46"21'00"E
L85	47.38	N46"21"00"F
L86	75.64	N7275'40"E
L87	140.00	N72"15"40"E
L88		N72"15'40"E \$71"53'30"W
L90		\$71°53'30"W
L9	118.00	S71"53'30"W S71"53'30"W S71"53'30"W
L92		S71*53'30"W
L94	69.92 30.96	N89*35'43"W
L95	104.86	NRQ'35'43"W
L97	105.12	NEOTOG'OO"W
L98		N60'09'00"W
L100	71.79	S64"48"00"W N82"58"16"W
L101	3.16	S71"53"30"W
L102	135.00	\$71"53"30"W \$71"53"30"W
L103	128.00	\$71"53'30"W
L104	118.00 118.00	\$71°53'30"W
L105	74.04	S71"53'30"W S71"53'30"W
L107	35.08	N89"22"53"W
L108	112.28 163.78	N89"22'53"W
L109	163.78 110.60	\$18"06'30"E N60"09'00"W
L110	66.01	N60"09'00"W
L112	120.00	N20°55'51"E
L113	130.00	N20"55"51"E
L114 L115	30.36	N20"55"51"E
L115	11.81 116.76	N46"21'00"E N46"21'00"E
L117	270.64	N7235'40"C
L118	62.14	S71"53"30"W
L119 L120	120.00 127.00	S71*53'30"W
L120	147.55	\$71"53'30"W \$71"53'30"W \$71"53'30"W
L122	169.36	S43'39'00'E1
L123	138.29	N46"21'00"E
L124	141.51 7.25	N46"21'00"E
L125	0.02	N65"11'00"E N72"28'00"E
L127	0.21	S1719'30'E
L128	319.73 890.13	S16'06'30"E
L129	890.13 2167.73	N60,00,00,M
L131	43.50	N46"21"00"E S43"39"00"E
1132	23.00	N46"21"00"E S17"32"00"E
	86.95	\$17'32'00"E
L134 L135	39.05	N17'44'20"W
L136	116.35	N17"44"20"W S59"43"00"W
L137	1171.43	S71°53'30"W
L138	171.84	N22'39'20"W
L139	4.50 64.53	N67'44'30"E N67"25'30"W
L141	113.871	N67"25'30"W S21"42'30"E
L142	123,66	S21"42'30"E
L143	121.00	\$2512'00"E
L144 L145	30.01 91.75	N17'32'00"W
L145	50.00	N72'40'30"E N17'19'30"W
L147	19.69	N17"19'30"W N72'40'30"E
L148	198.10 145.50	N17'44'20"W
L149 L150	75.50	S47"24'50"E N59"43'00"E
L150	75.56 140.32	N59"43"00"E N00"22"07"E
L152	140.32 28.55	N62"51"54"W
L153	44.85	
L154	258.66	
L156	157.69 152.06	\$86*39'15"E \$21*42'30"E
L157	275.13	N6817'30"E
L158	568.92	S71*53'30"W
L159 L160	135.82 171.12	N89'35'43"W
L161	250.00	N60"09"00"W N20"55"51"E
L162	274.55	571'53'30"W
L163	255.00	N71"53'30"F
L164 L165	279.80	N46"21"00"E1
L166	272.88 420.49	S72"15'40"W
L167	237.54	\$72"15"40"W N68"17"30"E \$21"42"30"E
	82.64	
L168	332.86	N46"21"00"E
L168		
L168 L169 L170	105.15	S46"21'00"W
L168 L169 L170 L171 L172	105.15 105.15 24.30	N46"21'00"E
L168 L169 L170 L171 L172 L173	105.15 105.15 24.30 24.30	N46"21'00"E S32"51'47"W N32"51'47"E
L168 L169 L170 L171 L172 L173	105.15 105.15 24.30 24.30 117.80	N46"21'00"E S32"51'47"W N32"51'47"E N63"10'05"E
L168 L169 L170 L171 L172 L173	105.15 105.15 24.30 24.30	N46"21'00"E S32"51'47"W N32"51'47"E


CUDIE	I DUCTI	DADUIC	CURVE TA		OLIODO T	011000 010
CURVE	LENGTH 39.27	RADIUS	DELTA	TANGENT	CHORD	CHORD DIR.
C2	39.27	25.00		25.00	35.36	\$2715'40'
	37.75	25.00		25.00	35.36	\$7012'00
C3		25.00		23.52	34.26	S21'32'45'
C4	39.27	25.00		25.00	35.36	562'44'20
C5	173.48	325.00		88.86	171.43	538'50'32'
C6	152.59	325.00		77.73	151.19	\$67'35'03'
C7	88.72	175.00		45.34	87.77	57979'25'
C8	9.72	175.00		4.86	9.72	N84'33'43'
C9	54.84	125.00		27.87	54.40	N84"27"37
C10	57.20	175.00	18'43'37"	28.86	56.94	\$8175'19"
C11	21.59	175.00	7"04"04"	10.81	21.57	N85"50"51"
C12	67.70	175.00		34.28	67.27	N7173'55"
C13	83.42	275.00	17"22'51"	42.03	83.10	N51'27'35'
C14	98.04	275.00	20"25"34"	49.54	97.52	N32'33'22'
C15	97.66	275.00	20"20"51"	49.35	97.15	N1210'10'
C16	105.95	275.00	22"04"25"	53.64	105.29	N09'02'29
C17	108.03	275.00		54.72	107.34	N3179'56
C18	135.67	275.00	28"15"58"	69.24	134.30	N56'43'09
C19	48.87	275.00		24.50	48.81	N75'56'36
C20	131.13	125.00		72.32	125.20	\$50'58'57"
C21	105.30	325.00	18'33'51"	53.12	104.84	N3012'47
C22	38.88	325.00	6"51"18"	19.47	38.86	N42'55'21'
C23	72.74	525.00		36.43	72.68	N5079'10'
C24	120.26	525.00	7*56'19" 13*07'29"	60.40	120.00	N60'51'04'
C25	44.42	525.00		22.22	44.40	
C26	30.24	75.00	4'50'51"	15.33	30.04	N69"50'14" N48'35'52"
C27	64.06	75.00	23"06'15"	34.13	62.13	
			48'56'18"			N12'34'36"
C28	77.53	75.00	59"13'44"	42.63	74.12	N41'30'25
C29	12.98	75.00	9"54'46"	6.50	12.96	N76'04'41'
C30	70.31	125.00	32"13"44"	36.11	69.39	S80'54'52"
C31	76.78	175.00	25"08'14"	39.02	76.16	N84'27'37'
C32	40.86	125.00	18"43"37"	20.61	40.67	S81"15'19"
C33	26.98	125.00	12"22"00"	13.54	26.93	N66"20'00"
C34	90.73	225.00	23"06"15"	45.99	90.12	N48'35'52"
C35	192.18	225.00	48"56'18"	102.39	186.39	N12'34'36"
C36	232.59	225.00	59"13"44"	127.89	222.37	N41'30'25'
C37	38.93	225.00	9"54'46"	19.51	38.88	N76'04'41"
C38	93.41	175.00	30"35"01"	47.85	92.31	\$38*50'32*
C39	82.16	175.00	26"54"01"	41.85	81.41	S67'35'03"
C40	122.00	275.00	25"25"09"	62.02	121.00	N33'38'26"
C41	214.81	475.00	25*54'40"	109.27	212.99	N59"18'20"
C42	71.66	133.50	30'45'21"	36.72	70.80	S52'02'49"
C43	34.86	133.50	14"57"39"	17.53	34.76	52971'19'
C44	99.86	111.50	51"19'00"	53.56	96.56	N41"46"00"
C45	36.79	125.00	16"51"53"	18.53	36.66	NB0*56*56*
C46	14.86	325.00	2"37"10"	7.43	14.86	S2274'26"
C47	8.00	175.00	2"37"10"	4.00	8.00	S22"14'26"
C49	98.77	616.07	9"11"11"	49.49	98.67	\$53'43'45"
C50	294.63	1410.00	11"58'20"	147.85	294.09	N52"20'10"
C51	50.54	184.00	15'44'12"	25.43	50.38	N38'28'54"
C52	179.93	452.73	22'46'16"	91.17	178.75	S41*59'56"
C53	194.69	1721.88	6'28'42"	97.45	194.59	N50'08'43"
C54	101.87	77.38	75"25"52"	59.84	94.67	N0513'43"
C55	82.56	60.00	78°50'13"	49.32	76.20	S06'55'54"
C56	49.43	210.00	13"29"13"	24.83	49.32	N39'36'24"
C57	171.99	190.00	51°51'55"	92.39	166.18	S58'47'45"\
C58	180.81	513.15	20"11"20"	91.35	179.88	
C59	166.85	160.00		91.91	159.40	N74'38'02"
C60	133.31	140.00	59"45"01"	72.20	128.33	N34'39'52"
C61	173.77	493.15	54'33'31"	87.79	172.87	N37'15'37"
C62	190.10	210.00	2011'20"	102.12	183.67	N74'38'02"
			51'51'55"			\$58'47'45"\
C63	44.72	190.00	13'29'13"	22.47	44.62	N39'36'24"
C64	110.08	80.00	78°50°13°	65.76	101.60	S06*55'54"\
C65	74.90	57.38	74'47'24"	43.86	69.70	N04'54'29"
C66	191.69	1701.88	6"27"12"	95.95	191.59	N50'09'28"
C67	187.88	472.73	22'46'16"	95.20	186.65	S41"59'56"\
C68	45.04	164.00	15"44"12"	22.66	44.90	N38'28'54"
C69	290.45	1390.00	11"58'20"	145.75	289.92	N52*20'10*8
C70	101.98	636.07	9"11"11"	51.10	101.87	S53'43'45"V
C71	184.81	75.00	141"11"04"	212.88	141.48	N10'26'32"


u	90,00,00	25.00	35.36	S62'44'20'E			100	-
0	30'35'01"	88.86	171.43	\$38*50'32"W				Г
0	26"54"01"	77.73		S67'35'03"W			N	-
	29"02"50"	45.34		\$79"19"25"W			12-28-12	17/06/10
0	310'54"	4.86	9.72	N84'33'43"W			1	1
0	25"08"14"	27.87	54.40	N84"27"37"E			181	9
미	18'43'37"	28.86	56.94	\$8175'19"W			11	1
D	7"04"04"	10.81	21.57	N85"50"51"W			2	C
0	22'09'49"	34.28	67.27	N7173'55"W			-	۳
Þ	17"22"51"	42.03	83.10	N51"27"35"W				
2	20"25"34"	49.54	97.52	N32'33'22"W			1 1	
2	20"20"51"	49.35	97.15	N12"10"10"W				C
2	22'04'25" 22'30'29"	53.64	105.29	N09"02'29"E			EIS	000
1	22'30'29"	54.72	107.34	N31"19'56"E			ш	_
4	28"15"58" 10"10"55"	69.24	134.30	N56'43'09"E	- 1		0	
4	1070'55"	24.50	48.81	N75"56'36"E	- 1		z	
4	60"06"12"	72.32	125.20	\$50"58"57"W			5	
4	18'33'51"	53.12	104.84	N301247 E			PLANS	
4	6"51"18"	19.47	38.86	N42"55"21"E	- 1			
1	7"56'19" 13"07'29"	36.43	72.68	N50"19"10"E			님	
1	13'07'29"	60.40	120.00	N60"51"04"E			RECORD	COMMENTO
4	4"50"51"	22.22	44.40 30.04	N69"50'14"E	- 1		9	Z
7	23'06'15"	15.33		N48'35'52"W	- 1		12	u
+	48'56'18"	34.13 42.63	62.13	N12"34"36"W	1		8	₹
+	59"13"44"		74.12	N41'30'25"E			8	É
+	9"54'46"	6.50	12.96	N76"04'41"E	- 1			5
+	32"13"44"	36.11 39.02	69.39 76.16	S80*54*52*W			No.	
+	25"08'14"	20.61	40.67	N84"27"37"E	- 1		CORRECT C-BSL	DWNVHID
+	18'43'37" 12'22'00"	13.54	26.93	S81'15'19"W				Į
+		45.99	90.12	N66"20"00"W	- 1		0	5
+	23'06'15" 48'56'18"	102.39	186.39	N48'35'52"W N12"34'36"W	- 1		-	ŝ
+	59"13"44"	127.89	222.37	N12'34'36 W	- 1		9	ć
+	9"54"46"	19.51	38.88	N76"04'41"E	- 1		12	-
t	30"35"01"	47.85	92.31		- 1		2	œ
H	26"54"01"	41.85	81.41	S38*50'32"W S67*35'03"W	- 1		0	250
۲	25"25"09"	62.02	121.00	N33'38'26"E	- 1	- 1	9	7
۲	25'54'40"	109.27	212.99	N5918'20"E	- 1		1	_
t	30'45'21"	36.72	70.80	S52'02'49"E			↲	(
t	14"57"39"	17.53	34.76	S2971'19*E				_
t	51"19"00"	53.56	96.56	N41"46"00"W	- 1			
t	16"51"53"	18.53	36.66	NB0"56"56"W	- 1			
t	2"37"10"	7.43	14.86	S22"14'26"W	- 1	(7	
T	2"37"10"	4.00	8.00	S22"14'26"W	- 1	U -	7	
T	9"11"11"	49.49	98.67	S53'43'45"W	- 1	Ž	=	
Г	11"58'20"	147.85	294.09	N52"20'10"E	- 1	= 1	<u>.</u>	
Г	15'44'12"	25.43	50.38	N38'28'54"E	- 1	4	ш	
	22'46'16"	91.17	178.75	S41°59'56"W	- 1	5 4	_	
Г	6"28'42"	97.45	194.59	N50'08'43"E		3 7	5	
Ľ	75"25"52"	59.84	94.67	N0513'43"E	- 1	₫ 3	7	
Ľ	78'50'13"	49.32	76.20	S06'55'54"W	- 1	ய	ū	
Ĺ	13'29'13"	24.83	49.32	N39'36'24"E	- 1	<u> </u>		
Ĺ	51°51'55" 20°11'20" 59°45'01"	92.39	166.18	S58'47'45"W	- 1	S	770	
L	20"1"20"	91.35	179.88	N74'38'02"E	- 1	0		
L	59"45"01"	91.91	159.40	N34'39'52"E	- 1	Z	Ž	
	54"33"31"	72.20	128.33	N37'15'37"E	- 1	₹ =)	
	20"11"20" 51"51"55"	87.79	172.87	N74'38'02"E	- 1	O F	-	
L	51"51"55"	102.12	183.67	S58'47'45"W	- 1	7 ()	
L	13"29"13"	22.47	44.62	N39'36'24"E	- 1	£ 1	_	
	78°50'13°	65.76	101.60	S06*55'54"W	- 1		=	
	74'47'24"	43.86	69.70	N04'54'29"E	- 1	<u> </u>	_	
	6"27"12"	95.95	191.59	N50°09'28"E	- 1	> ×	2	
	22'46'16"	95.20	186.65	S41"59'56"W	- 1	SIS	5	
_	15*44'12"	22.66	44.90	N38"28"54"E	- 1	Ž		
	11"58'20"	145.75	289.92	N52"20"10"E	- 1	田品	_	
_	9"1"11"	51.10	101.87	S53'43'45"W	- 1	I	2	
-	41'11'04"	212.88	141.48	N10"26'32"E	- 1	H (3	
_	60'06'12"	188.03	325.51	S50*58'57"W	- 1	P S	3	
						COMPREHENSIVE LAND AND SITE PLANNING		


H. EDWA	and ASSOX
ALLEN DRIVE ALLEN TOWNSHIP AND COUNTY VANIA	PLAN - LINE/CURVE TABLES


S, P.C
OWARD F
H. El


















NOTE:
LENGTH SHOWN ON PROFILES FOR SANITARY SEWER ARE FROM
CENTER OF MANHOLE TO CENTER OF MANHOLE. PERCENT SLOPES
ARE CALCULATED FROM INSIDE OF WALL OF UPSTREAM MANHOLE
TO INSIDE WALL OF DOWNSTREAM MANHOLE. H-2 STA 0+69.77 RIM 440.93 INV. IN 437.00 INV. OUT 437.00 H-4 STA 3+61.03 RIM 450.18 INV. IN 446.00 INV. OUT 446.00 F-3 STA 12+43.56 RIM 458.02 INV. IN 454.30 INV. OUT 454.30 GRATE 446.22 INV. OUT 442.22 NEW N ₩ 2 2 2 500 LEN 32' SLOPE 1.35% DIA. 15 IN. HDPE LEN 32' SLOPE 1.89% DIA. 15 IN. HDPE LEN 32' SLOPE 0.79% DIA. 15 IN. HDPE LEN 32' SLOPE 0.79% DIA. 15 IN. HDPE H-3 514 0-6983 INV. OUT 437.40 H-1 1-0.307 SIM 441.11 INV. IN 436.55 INV. OUT 436.55 3+61.01 450.18 OUT 446.60 F-3A STA 13+75 RIM 462.81 (2° SI INV. IN 453.59 INV. OUT 453.59 G-1 STA. 8+21.84 GRATE 446.22 INV. IN 442.50 INV. OUT 442.50 G-5 MODIFED IN STA 9+65.39 RIM 445.06 INV. IN 440.75 INV. IN 435.00 INV. OUT 434.58 G-3 STA. 9+16.94 GRATE 444.72 INV. IN 441.2 INV. IN 441.2 INV. OUT 441 F-4 STA 12+42.91 RIM 458.00 INV. OUT 454. 465.1 N N STA NV. STA 0+00 PENNINGTON PVI STA = 15+38 PVI ELEV = 463.84 A.D. = -4.41 K = 68.07 ENGINEERING COMPREHENSIVE LAND AND SITE PLANNING □ LANDSCAPE ARCHITECTURE - 225.0' VC -LOW POINT ELFV = 441.26 LOW POINT STA = 0+69.79 PM STA = 1+00 PM ELEV = 440.06 A.D. = 6.00 K = 30.15 SLOPE 0.51% LEN 107' LEN 36' SLOPE 0.50% DIA. 18 IN. HDPE DIA. 18 IN. HDPE H50 H CONSTRUCTION PLAN PHASES 1 & 2


R PENNINGTON
LOCATION: UDPER ALLEN TOWNSHIP
CUMBERLAND COUNTY
PENNSYLVANIA


PROFILE - PENNINGTON DRIVE SLOPE 0.53% LEN 301.36 LEN 46' SLOPE 0.97% DIA. 15 IN. HDPE LEN 289.64 SLOPE 1.07% SYSTEM J CROSSING PF6 12+57 458.98 IN 448.65 OUT 448.55 PF10 14-06.97 464.00 IN 454.10 OUT 454.00 PF5 11+84 455.26 IN 448.47 OUT 446.37 HON NEW ¥\$≣≹≩ # SESS ¥\$€\$€ DATUM ELEV 430.00 447.4 STA 441.41 RIM INV. 449.2 445.10 444.6 463.09 449.6 12+00 PENNINGTON DRIVE


SCALE:

HORIZ. 1" = 50'
VERT. 1" = 5' 19 OF 36









SEWER & WATER CROSSING LEN 106,75' SLOPE 0,73% SLOPE 0,67% 2-51x66 IN. ELIP. CMP 2-51x66 IN. ELIP. CMP 430	LEN 159' SLIDPE 1.35% DIA 18 IN, HDPE LEN 9 SLOPE 1.81% DIA. 18 IN, HDPE 430	SLOPE 0.82X SLOPE 38 80% DIA 18 IN. HOPE DIA 1	SET STATE OF	150 LEN 47' SLOPE 0.50% 2-42 IN. CMP	ENGINEERING □ ENGIN
00 3+00 4+00	DATUM RISU 480.00 10 10 10 10 10 10 10 10 10	0+00 HW-J TO EW-J SCALE: HORIZ 1' = 50' VERT. 1' = 5'	BASIN A OUTFALL OS-H TO EW-H2 SCALE: HORIZ, 1" = 50' VERT. 1" = 5'	BASIN B OUTFALL OS-F TO EW-F2 SCALE: HORIZ. 1" = 50' VERT. 1" = 5'	□COMPREHENSIVE LAND AND SITE PLANNING □LANDSCAPE ARCHITECTURE □ ENGINEERING 2403 Neath front Steres = Harrisburg, Pressnykania 17110 Telephone (717233-1026 FAX (7172)
EN 144' SOPE 0.82X O IN. ELIP. Culp 3+00 4+00					DRAWN BY: EIS CONSTRUCTION PLAN PHASES 1 & 2 CHECKED BY: JAK PENNINGTON UPPER ALLEN TOWNSHIP SCALE: AS NOTED CLIMBERLAND COUNTY PENNISTLYANIA JOB NUMBER: 06018 PROFILES - STORM WATER AND ASSOCIATES, P.C.

SLOPE 1.79% 46×60 IN. ELIP. CMP


HW-G TO EW-G EAST


SCALE:


HORIZ. 1" = 50'


VERT. 1" = 5'


DATUM ELEV 425.00























DEP STANDARD CONSTRUCTION DETAIL #1
Vegetated Channels




CHANNEL NO.	STATIONS	BOTTOM WIDTH B (FT)	DEPTH D (FT)	Z1 (FT)	Z2 (FT)	LINING*
1.1	0+00 - END	3	1	3	3	TRM 435
1.2	0+00 - END	3	1	3	3	TRM 435
1.3	0+00 - END	5	1	3	3	JUTE
2	0+00 - END	7	1.5	3	3	TRM 435
3.1	0+00 - END	5	2	3	3	TRM 435
3.2	0+00 - END	5	2	5	5	TRM 450
4.1	0+00 - END	10	2.1	3	3	TRM 450
4.2	0+00 - END	10	1.5	3	3	TRM 450
5	0+00 - END	6	1	3	3	TRM 435
6	0+00 - END	5	1	2	2	TRM 435
7	0+00 - END	4.5	0.75	3	3	JUTE

* SEE MANUFACTURER'S LINING INSTALLATION DETAIL FOR STAPLE PATTERNS, AND VEGETATION STABILIZATION SPECIFICATIONS FOR SOIL AMENDMENTS, SEED MIXTURES, AND MULCHING INFORMATION.








		RIP	RAP	APRON					
OUTLET NO.	PIPE DIA Pd (IN)	SIZE (R)	THICK. Rt (IN)	LENGTH AI (FT)	INITIAL WIDTH Aiw (FT)	TERMINAL WIDTH Atw (FT)			
A	18	R-3	9"	14	4.5	10.1			
C	24	R-3	9"	9	6	9.6			
D	36	R-4	18"	42	9	25.8			
E	42	R-3	9"	14	10.5	16.1			
F	18	R-3	9"	7	4.5	7.3			
G	51 X 66	R-4	18"	22	15	23.8			
H	18	R-3	9"	7	4.5	7.3			
J	18	R-3	9"	7	4.5	7.3			

RIPRAP APRONS AT PIPE OUTLETS WITH FLARED END SECTIONS SECTION SCALE: NOT TO SCALE



PLAN MEW DISCHARGE HOSE FILTER BAG* WELL VEGETATED, GRASSY AREA ELEVATION VIEW

FILTER BAGS SHALL BE MADE FROM NON-WOVEN GEOTEXTILE MATERIAL SEWN WITH HIGH STRENGTH, DOUBLE STITCHED "J" TYPE SEAMS. THEY SHALL BE CAPABLE OF TRAPPING PARTICLES LARGER THAN 150 MICRONS.


A SUITABLE MEANS OF ACCESSING THE BAG WITH MACHINERY REQUIRED FOR DISPOSAL PURPOSES MUST BE PROVIDED. FILTER BAGS SHALL BE REPLACED WHEN THEY BECOME & FULL SPARE BAGS SHALL BE KET? AVAILABLE FOR REFLACEMENT OF THOSE THAT HAVE FAILED OR ARE


THE PUMPING RATE SHALL BE NO GREATER THAN 750 GPM OR \$\frac{1}{2}\$ THE MAXIMUM SPECIFIED BY THE MANUFACTURER, WHICHEVER IS LESS, PUMP INTAKES SHOULD BE FLOATING AND SCREAMED.



TYPICAL E AND S CONTROL FOR INDIVIDUAL LOTS INSTALL FIRST FABRIC FROM EN ON LOW SIDE FLOTS. CLEAR AND GRUB NO MORE THAN NECESSARY FOR CONSTRUCTION. DISPOSE OF DEBRIS IN APPROVED MANNER. STREP AND STOCKPILE TOPSOIL. SEED IMMEDIATELY. PLACE GRUSHED ACORGOATE BASE IN DRIVEWAY.

CONSTRUCT DIVELLING. ESTREAMS OF THE ACTION OF THE






INDIVIDUAL LOT EROSION CONTROL MEASURES VIEWS AS NOTED SCALE: NOT TO SCALE

ENGINEERING SITE PLANNING

AND

30 OF 36





- Earthen berm shall be maintained until roadway is stoned. Road subbase berm shall be maintained until roadway is paved.
- ** Six inch minimum height asphalt berm shall be maintained until roadway surface receives final coat.

One acre maximum drainage area with 15" overflow pipe and 4" head.



STORM INLET PROTECTION AND BERM(S) -- CURBED ROADWAY SECTION SCALE: NOT TO SCALE





NOT TO SCALE

TRENCH EXCAVATION PROCEDURES

TRENCH EXCAVATION SHALL COMPLY WITH THE FOLLOWING:

- 1. EXCAVATION MATERIAL SHALL BE PLACED IN SUCH A MANNER AS NOT TO OBSTRUCT NATURAL DRAINAGE CHANNELS.
- WHERE POSSIBLE, EXCAVATED MATERIAL SHALL ALSO BE PLACED ON THE UPHILL SIDE OF THE TRENCH TO DIRECT WATER AWAY FROM THE TRENCH.
- 3. WHERE RUNOFF FROM TRENCHES OR SOIL PILE WILL ENTER THE STORM SEWERS, STORM DRAIN INLET CONTROLS SHALL BE IMPLEMENTED.
- 4. BACKFILLING OF THE TRENCH WILL FOLLOW THE LAYING OF THE PIPE AS CLOSELY AS POSSIBLE.
- THE TRENCH SHALL BE BACKFILLED TO ABOVE GROUND LEVEL TO A HEIGHT WHICH WILL INSURE COMPLETE FILLING OF THE TRENCH UPON SETTLEMENT.
- 6. IMMEDIATELY AFTER BACKFILLING THE TRENCH, THE CONTRACTOR SHALL RESTORE THE SURFACE WITH
- TOPSOIL, MULCH AND SEED.
 SPECIFIED CRUSHED STONE OR
 WHERE THE TRENCH IS IN A PAVED AREA, MAINTAIN A LAYER OF STONE ON THE TOP OF THE TRENCH UNTIL THE FINAL PAVING IS
 COMPLETED.
- THE CONTRACTOR SHALL REFILL ANY TRENCHES IN WHICH SETTLEMENT CAUSES A DEPRESSION WHICH ALTERS THE DRAINAGE CHARACTERISTICS OF THE AREA, FOR THE DURATION OF THE "MAINTENANCE PERIOD".

UPON COMPLETION OR TEMPORARY CESSATION OF THE EARTH DISTURBANCE ACTIVITY, OR ANY STAGE THEREOF, THE PROJECT SITE SHALL BE IMMEDIATELY STABILIZED. DURING NON-GERMINATING PERIODS, MULCH MUST BE APPLIED AT THE RECOMMENDED RATES. AREAS NOT AT FINISHED GRADE AND THAT MILL BE RE-DISTURBED WITHIN ONE YEAR MAY BE SEEDED WITH A QUICK GROWING TEMPORARY SEED MIXTURE. ALL AREAS AT FINISHED GRADE OR THAT MILL NOT BE RE-DISTURBED WITHIN ONE YEAR MAY BE SEEDED WITH A PERMANENT SEED MIXTURE.

SWALE OPERATION & MAINTENANCE SCHEDULE:

- GRASS IN THE STORMWATER BASIN AND ON THE EMBANKMENT SHALL BE MOWED ON A REGULAR BASIS TO PREVENT BRUSH AND
 TREE GROWTH.

 CULVERTS AND SWALES SHALL BE CHECKED MONTHLY FOR OBSTRUCTIONS, SEDIMENTATION AND WASHOUTS.

 THE SWALES SHALL BE CHECKED MONTHLY FOR RODENTS THAT MAY INTERFERE WITH THE STRUCTURAL INTEGRITY.

 UPON FINDING ANY COMPONENT OF THE DRAINAGE STRUCTURES NOT FUNCTIONING AS INTENDED, THAT PORTION OF THE STRUCTURE
 SHALL BE IMMEDIATELY CLEANED, REPAIRED OR REPLACED.


INFILTRATION TRENCH OPERATION & MAINTENANCE SCHEDULE:

- CRASS SIDE SLOPES SHALL BE MOWED ON A REGULAR BASIS. REMOVE ANY INVASIVE PLANTS AS NEEDED.

 DO NOT APPLY PESTICIDES OR FERTILIZERS IN OR AROUND INFILITRATION STRUCTURES.

 THE INFILITRATION TRENCH SHALL BE CHECKED MONTHLY FOR DESTINCTIONS, TASSH, SEDIMENTATION AND WASHOUTS.

 THE INFILITRATION TRENCH SHALL BE CHECKED MONTHLY FOR ROBENTS THAT MAY INTERFERE WITH THE STRUCTURAL INTEGRITY OF THE CETULATURE.
- UPON FINDING ANY COMPONENT OF THE BERM NOT FUNCTIONING AS INTENDED, THAT PORTION OF THE STRUCTURE SHALL BE IMMEDIATELY CLEANED, REPAIRED OR REPLACED.



NOTES:

- 1. FILTER SOCKS TO BE FILTREXX SILTSOXX OR APPROVED EQUAL:
- FILTREXX INTERNATIONAL, LLC 35481 GRAFTON EASTERN GRAFTON, OH 44044 440-926-8041
- 440-926-4021 (FAX) WWW.FILTREXX.COM
- 2. PLACE ALONG CONTOUR AS SHOWN IN PLAN AND STAKE PER DETAIL.
 3. THAN EMBE BUPHILL AND STAKE TO SECURE.
 3. FILL WITH COMPOST DEETING THE FOLLOWING REQUIREMENTS:
 A. PH. 5.0-8.0
 B. PARTICLE SIZE BETWEEN ½" AND 2"
 C. MOISTRUE CONTENT OF LESS THAN 60%

- . MATERIAL SHALL BE RELATIVELY FIRE (<1% BY DRY WEIGHT) OF INERT OR FOREIGN MAN MADE MATERIALS.

 A SAMPLE SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL PRIOR TO BEING USED AND MUST
 COMPLY WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.



SILTSOXX MAINTENANCE:

1. THE CONTRACTOR SHALL MAINTAIN THE SILTSOXX(TM) IN A FUNCTIONAL CONDITION AT ALL TIMES AND IT SHALL BE ROUTINELY INSPECTED.

2. WHERE THE SOXX(TM) REQUIRES REPAIR, IT MILL BE ROUTINELY REPAIRED.

3. THE CONTRACTOR SHALL REMOVE SEDIMENT COLLECTED AT THE BASE OF THE SOXX(TM) WHEN THEY REACH 1/2 OF THE EXPOSED HEIGHT OF THE SOXX(TM), OR AS DIRECTED BY THE ROINEER. ALTERNATIVELY, RATHER THAN CREATE A SOIL DISTURBING ACTIVITY, THE ENGINEER MAY CALL FOR ADDITIONAL SOXX(TM) TO BE ADDED AT AREAS OF HIGH SEDIMENTATION, PLACED IMMEDIATELY ON TOP OF THE EXISTING SEDIMENT LADEN SILTSOXX(TM).

THE SILTSOXX(TM) WILL BE DISPERSED ON SITE WHEN NO LONGER REQUIRED. AS DETERMINED BY THE ENGINEER.


		PERIMETER MAXIMUM DRAINAGE AR BASED ON SLOPE LENGTH & RECOMMENDED DIAMETER SOXX							
SLOPE		8"	12"	18"	24"				
0-2%	FLATTER THAN 50:1	125	250	300	350				
2-10%	50: 1-10: 1	100	125	200	250				
10%-20%	10:1-5:1	75	100	150	200				
20%-33%	3:1-2:1	50**	50	75	100				
>50%	>2:1	25**	25	50	75				

SEE INDIVIDUAL SPECS FOR PROPER USE
 ONLY TO BE USED IN CONJUNCTION WITH COMPOST BLANKETS

IN CASE OF SILTSOXX(TM) FAILURE, THE FOLLOWING TABLE SHALLBE USED TO DETERMINE APPROVED REPLACEMENT BMP.

SILTSOXX(TM) REPLACEMENT GUIDE


SILTSOXX DIAMETER	EQUIVALENT STANDARD FILTER FABRIC FENCE
8"	18" SILT FENCE
12"	30" SILT FENCE
18"	SUPER SILT FENCE
24"	SUPER SILT FENCE



ENVIRONMENTAL DUE DILIGENCE

ENVIRONMENTA, DE DISCRICE MUST SE PERFORMED TO SETRIMINE IF THE FILL LATERIALS ASSOCIATED WITH PRACECT OF AUTHOR ASSOCIATION OF THE PRACECT OF

DEP STANDARD CONSTRUCTION DETAIL #12





					RISER		A Second		BAR	REL		EMBAN	KMENT		
TRAP	Z1 (FT)	Z2 (FT)	MAT'L	DIA Dr (IN)	CREST ELEV RCE (FT)	BOT. PERF. ELEV (FT)	MAT'L	DIA Db (IN)	BIE (FT)	LENGTH BI (FT)	OUTLET ELEV BOE (FT)	TOP ELEV ETE (FT)	WIDTH Etw (FT)	CLEAN OUT ELEV COE (FT)	BOTTOM ELEV BE (FT)
Α	3	3	CMP	42"	433 50	431.23	CMP	30°	430.0	29	429.71	436.0	6'	431.23	4300

		CONCRETE BASE		OUTLET BASIN						
TRAP NO.	LENGTH CBI (IN)	WIDTH CBW (IN)	THICKNESS CBI (IN)	RIPRAP SIZE (R-)	DEPTH D (IN)	WIDTH OBW (FT)	LENGTH OBL (FT)			
A	48"	48"	15"	R-4	24"	7.6'	15'			

Clean out stakes shall be placed near center of trap. Accumulated sediment shall be removed when it reaches the clean out mark on the stake.

Wherever it is necessary to totally dewater a barrel/riser type trap, the riser should be designed according to the sp shown in Standard Construction Detail #13.






NOTE: SHOW ALL DETAILS AND CONSTRUCTION DIMENSIONS ON PLAN DRAWINGS.

FILTER FABRIC FENCE MUST BE INSTALLED AT EXISTING LEVEL GRADE. BOTH ENDS OF EACH FENCE SECTION MUST BE EXTENDED AT LEAST 8 FEET UPSLOPE AT 45 DEGREES TO THE MAIN FENCE ALLEMENT.

ANY FENCE SECTION WHICH HAS BEEN UNDERMINED OR TOPPED MUST BE IMMEDIATELY REPLACED WITH A ROCK FILTER DUTLET. SEE STANDARD CONSTRUCTION DETILAL #18.

REINFORCED FILTER FABRIC FENCE (30" HIGH)
SECTION SCALE: NOT TO SCALE

DEP STANDARD CONSTRUCTION DETAIL #19 STANDARD FILTER FABRIC FENCE (18" HIGH)




* STAKES SPACED • 8" MAXIMUM. USE 2" X 2" WOOD OR EQUIVALENT STEEL STAKES.

FILTER FABRIC FENCE MUST BE PLACED AT LEVEL EXISTING GRADE. BOTH ENDS OF THE BARRIER MUST BE EXTENDED AT LEAST 8 FEET UP SLOPE AT 45 DEGREES TO THE MAIN BARRIER AUDOMBENT.

SEDIMENT MUST BE REMOVED WHEN ACCUMULATIONS REACH 1/2 THE ABOVE GROUND HEIGHT OF THE FENCE.

ANY SECTION OF FILTER FABRIC FENCE WHICH HAS BEEN UNDERMINED OR TOPPED MUST BE IMMEDIATELY REPLACED WITH A ROCK FILTER OUTLET. SEE STANDARD CONSTRUCTION DETIAL #18.

STANDARD FILTER FABRIC FENCE (18" HIGH)
SECTION SCALE: NOT TO SCALE



** CHAIN LINK TO POST FASTENESS SPACED @ 14" MAX. USE NO.
CHAIN LINK TO TENSION WRE FASTENESS SPACED @ 60" MAX. USE
NO. 10 GA. GALMANIZED STEEL MIRE. FABRIC TO CHAIN FASTENERS
SPACED @ 24" MAX. C TO C.

NO, 7 GA. TENSION WIRE INSTALLED HORIZONTALLY AT TOP AND BOTTOM OF CHAIN-LINK FENCE.

FILTER FABRIC FENCE MUST BE PLACED AT EXISTING LEVEL GRADE.
BOTH ENDS OF THE BARRIER MUST BE EXTENDED AT LEAST 8 FEET
UPSLOPE AT 45 DEGREES TO THE MAIN BARRIER ALIGNMENT.

SEDIMENT MUST BE REMOVED WHEN ACCUMULATIONS REACH 1/2 THE ABOVE GROWND HEIGHT OF THE FENCE

SUPER FILTER FABRIC FENCE
SECTION SCALE: NOT TO SCALE

102.4(R)(5)(VI) *A SEQUENCE OF BMP INSTALLATION AND REMOVAL IN RELATION TO THE SCHEDULING OF EARTH DISTURBANCE ACTIVITIES, PRIOR TO, DURING AND AFTER EARTH DISTURBANCE ACTIVITIES.* (ALL TIMES ARE APPROXIMATE)

PLAN NOTES:

A. ALL EARTH DISTURBANCE ACTIVITIES SHALL PROCEED IN ACCORDANCE WITH THE FOLLOWING SEQUENCE. EACH STACE SHALL BE COMPLIANCE WITH CHAPTER TOZ REQULATIONS BEFORE ANY FOLLOWING STACE IS INITIATED. CLEARING AND GRUBBING SHALE E LIMITIO DAYLY TO MOSE AREAS ESCHRIED IN EACH STACE.

B. AT LEAST 7 DAYS BEFORE STARTING ANY EARTH DISTUBBANCE ACTIVITIES, THE OPERATOR SHALL CONTRACT ALL CONTRACTORS INVOLVED IN THOSE ACTIVITIES, THE LANDOWNER, ALL APPROPRIATE MUNICIPAL OFFICIALS, THE EROSION AND SEDUMENTATION CONTROL FLAM REPREMENTATIVE OF THE CUMBERHAND COUNTY CONSERVATION DISTRICT TO SOLDEDLE AN CONTROL FLAM FROM METERICA, ALSO, AT LEAST 3 DAYS BEFORE TAXING ANY EARTH DISTURBANCE ACTIVITIES, ALL CONTRACTORS INVOLVED INDEX. ALSO, AT LEAST 3 DAYS BEFORE TAXING ANY EARTH DISTURBANCE ACTIVITIES, ALL CONTRACTORS INVOLVED INDEX. ACTIVITIES, ALL DISTRICT METERICATION OF COLL SYSTEM, NO. AT 1-1000-242-1776 FOR

C. ALL EXCAYATION FOR UTILITY LINE INSTALLATION SHALL BE LIMITED TO THE AMOUNT THAT CAN BE EXCAYATED, INSTALLIB BACKFILLED AND STABILIZED WITHIN ONE MORNING DAY. ALL EXCAYATED MATERIAL SHALL BE DEPOSITED ON THE UPSLOPE OF THE TRIBON'S SHALL BE DEPOSITED ON THE UPSLOPE FOR THE REDIGHS SHALL BE PRUMPED THROUGH A DIRT BACKFILLED THE PROPERTY OF THE REDIGHS SHALL BE PRUMPED THROUGH A DIRT BACKFILLED THE PROPERTY OF THE PROPERTY OF

D. BEFORE IMPLEMENTING ANY REVISIONS TO THE APPROVED EROSION AND SEDIMENT CONTROL PLAN OR REVISIONS TO OTHER PLANS, WHICH MAY AFFECT THE EFFECTIVENESS OF THE APPROVED EAS CONTROL PLAN, THE OPERATOR MUST RECEIVE APPROVAL OF THE REVISIONS FROM THE CAUBERCHAND COUNTY CONSERVATION DISTRICT.

E. THE OPERATOR SHALL REMOVE FROM THE SITE, RECYCLE OR DISPOSE OF ALL BUILDING MATERIALS AND WASTES IN ACCORDAN WITH THE DEPARTMENT'S SOLID WASTE MANAGEMENT REGULATIONS AT 25 PA CODE 260.1 ET SEQ., 271.1 ET SEQ., AND 287.1 ET SEQ.

H. PLANTING AND SEEDING DATES EXTEND FROM MARCH 15TH TO OCTOBER 15TH. INTERIM STABILIZATION WILL BE ACHIEVED BY MULCHING

J. ONLY LIMITED DISTURBANCE WILL BE PERMITTED TO PROVIDE ACCESS TO (CONSTRUCT SEDIMENT TRAPS, DIVERSION TERRACES, ETC.) FOR GRADING AND ACQUIRING BORROW TO CONSTRUCT THOSE CONTROLS.

L SEDIMENT REMOVAL FROM E&SPC CONTROLS & FACILITIES SHALL BE DISPOSED OF IN LANDSCAPED AREAS OUTSIDE OF STEEP SLOPES, WETLANDS, FLOODPLAINS, OR DRAINAGE SWALES AND IMMEDIATELY STABILIZED, OR PLACED IN TOPSOIL STOCKPILES. AS SHOULD UNFORESED BROWN CONDITIONS DEVELOP DURING CONSTRUCTION, THE CONTRACTOR SHALL TAKE ACTION TO REMEDY SOURCE CONTRACTOR WOOD STATE OF SHALL TAKE ACTION TO REMEDY DISPLACEMENT, STOCKHELS OF WOOD STATE OF SHALL TAKE ACTION TO REMEDY SHALL SHALL BE HELD BY REMONES TO DEAL MINEDIATELY WITH DEMEDSACY PROBLESS OF EROSON.

N. THE CONTRACTOR IS ADVISED TO BECOME THOROUGHLY FAMILIAR WITH THE PROVISIONS OF THE APPENDIX 64, EROSION CONTROL ROLES AND REGULATIONS, TITLE 25, PART 1, DEPARTMENT OF ENVIRONMENTAL PROTECTION, SUBPART C, PROTECTION OF MARINAL RESOURCES, ARTICLE III, WATER RESOURCES, CATCLE III, WATER RESOURCES, CATCLE III, WATER RESOURCES, CATCLE III, WATER TOZ. RESOURCES, CATCLE III, WATER RESOURCES, CATCLE III, WATER TOZ. RESOURCES, CATCLE III, WATER RESOURCE

O. A COPY OF THIS EROSION AND SEDIMENTATION CONTROL REPORT AND PLANS MUST BE POSTED AT THE CONSTRUCTION SITE. CONSTRUCTION IS ANTICIPATED TO BEGIN FALL 2007 AND FINAL STABILIZATION TO BE ACCOMPLISHED BY FALL 2015. SEE COVER SHEET FOR PHASING DATES.

THE CONTRACTOR WILL SUBMIT WRITTEN NOTIFICATION TO CUMBERLAND COUNTY CONSERVATION DISTRICT AT LEAST 7 DAYS
PRIOR TO THE START OF CONSTRUCTION.

2. CONSTRUCT ROCK CONSTRUCTION ENTRANCE 1 & 2 AS SHOWN ON THE EROSION AND SEDIMENTATION CONTROL PLANS.

INSTALL THE FILTER FABRIC FENCE BELOW THE PROPOSED SEDIMENT TRAP & BASIN AS SHOWN ON THE EROSION CONTROL PLANS.

PLACE ALL SOIL MATERIAL REMOVED FROM THE SITE ON THE TOPSOIL STOCKPILE AREA. STOCKPILE HEIGHTS MUST NOT EXCEED 35 FEET AND SIDE SLOPES MUST NOT BE STEEPER THAN 2:1.

5. ROUGH GRADE SEDIMENT BASIN B AND SEDIMENT TRAP A LOCATED SOUTH OF PENNINGTON DRIVE

INSTALL THE PIPE FOR THE OUTLETS FROM THE SEDIMENT BASINS. INSTALL THE TEMPORARY RISERS AND SKIMMERS IN THE SEDIMENT BASINS.

FINE GRADE THE SEDIMENT BASIN/TRAPS EMBANKMENTS AND IMMEDIATELY INSTALL JUTE MATTING ON THE 3:1 SLOPES OUTSIDE
OF THE BASINS/TRAPS AND SYNTHETIC LINER ON THE BASIN SPILLWAY + TEMPORARY SWALE #6.

8. INSTALL THE RIPRAP OUTLET PROTECTIONS AT THE OUTLETS OF THE SEDIMENT BASIN OUTLET PIPES.

9. STRIP TOPSOIL FROM THE PROPOSED ROAD (PENNINGTON DRIVE).

10. INSTALL THE BYPASS SWALES (1-5), STORMPIPE SYSTEMS, AND THE REMAINDER OF THE FILTER FABRIC FENCE. (TAKE NOTE OF GRADING DIFFERENCES BETWEEN E&S PLAN & GRADING PLAN: CONTOURS SHOWN IN BOLD)

11. ROUGH GRADE THE ROAD (PENNINGTON DRIVE) IMMEDIATELY AFTER INSTALLATION OF E&S BMP*S

12. INSTALL THE REMAINDER OF THE STORM SEWER SYSTEMS. IMMEDIATELY INSTALL FILTER BAG INLET PROTECTIONS WITHIN THE INLETS AS THEY ARE INSTALLED.

13. INSTALL ALL OF THE SITE UTILITIES.

14. FINE GRADE THE ROAD.

15. PLACE THE STONE FOR THE INTERIOR ROADWAYS.

PERMANENTLY STABILIZE AREAS OUTSIDE OF THE PAVEMENT AREAS THAT HAVE BEEN DISTURBED AND ARE TO REMAIN AS GRASS.

17. COMPLETE ALL CONCRETE WORK, WHICH INCLUDES CURBS, SIDEWALKS ETC.

18. COMPLETE THE BASE COURSE PAVING

20. COMPLETE ALL LANDSCAPE PLANTINGS.

21. PERMANENTLY STABILIZE ALL DISTURBED AREAS INCLUDING ALL UNCULTIVATED AREAS IN THE OPEN SPACE LOTS.

22. COMPLETE THE WEARING COURSE PAVING.

23. MEET WITH CUMBERLAND COUNTY CONSERVATION DISTRICT FOR FINAL SITE INSPECTION.

24. AFTER APPROVAL OF STABILIZATION, REMOVE TEMPORARY EROSION AND SEDIMENTATION CONTROL MEASURES. PERMANENTLY STABILIZE ALL AREAS DISTURBED BY REMOVAL OF THE EROSION CONTROL MEASURES.

25. THE SEDIMENT TRAP MUST BE CONVENTED TO THE PERMANENT STORMWATER DETENTION BASIN AND UPSTREAM INFILITRATION BERM. REMOVE THE TEMPORARY RISER AND INSTAL THE PERMANENT TYPE M* INLET OUTLET STRUCTURE. REMOVE THE ORANGE CONSTRUCTION FEOCE AND INSTALL THE INFILITRATION BERM.

26. PERMANENTLY STABILIZE PERMANENT STORMWATER DETENTION BASIN A AND ANY REMAINING DISTURBED AREA

27. SEDIMENT BASIN B MUST BE CONVERTED TO THE PERMANENT STORMWATER DETENTION BASIN. REMOVE THE TEMPORARY RISERS AND INSTAL THE PERMANENT TYPE 'M' INLET OUTLET STRUCTURES.

28. THE OUTFALL FROM SYSTEM C MUST BE CONVERTED INTO AN INFILTRATION BERM. ADD MH C- EWC, REMOVE THE ORANGE CONSTRUCTION FENCE AND INSTALL THE INFILTRATION BERM. 29. PERMANENTLY STABILIZE PERMANENT STORMWATER DETENTION BASIN B AND ANY REMAINING DISTURBED AREAS.

TEMPORARY CONTROL MEASURES AND FACILITIES FOR USE DURING EARTHMOVING

THE TEMPORARY CONTROL MEASURES AND FACILITIES PROPOSED FOR THIS PROJECT INCLUDE SEDIMENT TRAP #1, SEDIMENT BASIN #1, FILTER FABRIC FENGING, TEMPORARY SEEDING, INLET PROTECTION, ROCK FILTERS, TEMPORARY SLOPE PROTECTION AND ROCK CONSTRUCTION ENTRANCE.

FOR LOCATIONS AND DIMENSIONS OF THESE TEMPORARY CONTROL MEASURES, SEE THE EROSION CONTROL PLANS AND DETAILS. PERMANENT CONTROL MEASURES AND FACILITIES FOR LONG TERM PROTECTION

THE PERMANENT CONTROL MEASURES AND FACULTES PROPOSED FOR THIS PROJECT INCLUDE STORMWATER MANAGEMENT FACULTIES, PREMIANENT SEEDING, PERMANENT CHANNEL MERS, AND INFILERATION FACULTES, PERMANENT SEEDING, PERMANENT CHANNEL MERS, AND RIPRAP OUTLET PROTECTION. FOR LOCATIONS AND DIMENSIONS OF THESE PERMANENT CONTROL MASSINES, SEE THE ATTROCHE WORKSPIETS, EROSING OVERTICE, PLANS ON DITAILS.

102.4(B)(5)(X) "A MAINTENANCE PROGRAM WHICH PROVIDES FOR INSPECTION OF BMPS ON A WEEKLY BASIS AND AFTER EACH MEASURABLE RAINFALL EVENT, INCLUDING THE REPAIR OF THE BMPS TO ENSURE EFFECTIVE AND EFFICIENT OPERATION."

TEMPORARY CONTROLS.

THE CONTROLS WILL BE RESPONSIBLE FOR THE INSTALLATION AND MAINTENANCE OF ALL THE TEMPORARY EROSION AND SEDIMENTATION MAGARIEST TO BE MELBERNIED AS PART OF CONSTRUCTION AS FOLLOWS, BUT NOT LIMITED TO:

2. DIVERSION CHANNELS, SEDIMENTATION BASINS, SEDIMENT TRAPS, AND STOCKPILES MUST BE STABILIZED IMMEDIATELY.

FILTER FABRIC FENCING:

FILTER FABRIC FENCE MUST BE INSTALLED AT LEVEL GRADE. BOTH ENDS OF EACH FENCE SECTION MUST EXTEND AT LEAST 8 FEET UPSLOPE AT 45 DEGREES TO THE MAIN FENCE ALIGNMENT.

3. ANY FENCE SECTION, WHICH HAS BEEN UNDERMINED OR TOPPED, MUST BE IMMEDIATELY REPLACED WITH A ROCK FILTER OUTLET. (SEE ROCK FILTER OUTLET DETAIL.)

4. WHERE ENDS OF FILTER FABRIC COME TOGETHER, THEY MUST BE OVERLAPPED, FOLDED AND STAPLED TO PREVENT SEDIMENT BYPASS. THE TOE ANCHOR MUST BE BACKFILLED AND COMPACTED TO A DENSITY EQUAL TO THE SURROUNDING SOILS. 5. THE FENCE MUST BE INSPECTED AFTER EVERY PRECIPITATION EVENT AND ON A WEEKLY BASIS. ANY NECESSARY REPAIRS WILL BE MADE IMMEDIATELY.

6. THE MANUFACTURER S RECOMMENDATIONS WILL BE ADHERED TO FOR REPLACEMENT OF THE FILTER FABRIC DUE TO WEATHERING

3. A CLEAN-OUT ELEVATION WILL BE CLEARLY MARKED IN THE FIELD TO INDICATE THE ELEVATION AT WHICH ACCUMULATED SEDIMENT SHOULD BE REMOVED.

4. SEDIMENT WILL NOT BE ALLOWED TO ENTER THE WATERS OF THE COMMONWEALTH DURING SEDIMENT REMOVAL OR DISPOSAL OPERATIONS

SEDIMENT MUST BE REMOVED FROM INLET PROTECTION AFTER EACH STORM EVENT, OR WHEN THE DISTANCE BETWEEN THE GRATE AND THE SEDIMENT LEVEL IS REDUCED TO 18".

ROCK FILTER OUTLETS:

1. SEDIMENT MUST BE REMOVED WHEN ACCUMULATIONS REACH 1/3 THE HEIGHT OF THE OUTLETS.

VEGETATIVE FILTER STRIP:

I. THE SUITABILITY OF NATURAL VEGETATIVE FILTER STRIPS MUST BE FIELD VERIFIED PRIOR TO THEIR APPROVAL

2. VEGATIVE FILTER STRIPS MAY BE USED TO REMOVE SEDIMENT FROM PROJECT RUNOFF THAT IS DIRECTED TO THE STRIP AS SHEET FLOW. 3. VEGETATION MUST BE AN EXISTING, WELL-ESTABLISHED, PERENNIAL GRASS. WOODED AND BRUSHY AREAS ARE NOT ACCEPTABLE.

ROCK CONSTRUCTION ENTRANCE:

PLANTING AND SEEDING DATES EXTEND FROM MARCH 15TH TO OCTOBER 15TH. INTERIM STABILIZATION WILL BE ACHIEVED BY MULCHING. AREAS TO BE TEMPORARLY SEEDED WILL BE PLANTED WITH RYEGRASS, LOUIUM SPECIES, (100%) AT A RATE OF 44 LBS. PER ADRE. BETOME TEMPORARLY SEEDING, FERTULZE WITH BASIC FERTULZER (5-5-5) AT A RATE OF 1000 LBS. PER ADRE AND LIME AT A RATE OF NOW (1) TON PER ADRE. TEMPORARLY SEEDED AREAS WILL BE FERTULZED WITH BASIC FERTULZER (7-02-20) AT A RATE OF 20 LBS. PE HIGUSAND SQUARE FEET (1,000 SO. FT.) MANIGARTLY BETOME SEEDING. ATTER SEEDING, THE TEMPORARILY SEEDED AREAS WILL BE WILCHED WITH WOOD CELLULOSE TERER AT A RATE OF THREE (3) TONS PER ADRE.

PLANTING AND SEEDING DATES EXTEND FROM MARCH 15TH TO OCTOBER 15TH. INTERIM STABILIZATION WILL BE ACHIEVED BY MULCHING. THE OWNER WILL BE RESONABLE FOR THE MAINTENANCE OF ALL PERMANENT EROSION AND SEDMENTATION CONTROL MEASURES AFTER CONSTRUCTION 15 COMPLETED.

ALL SEEDS, AS SPECIFIED WILL CONFORM TO THE PENNSYLVANIA SEED ACT OF 1965, AS AMENDED, AND REGULATIONS OF THE PENNSYLVANIA DEPARTMENT OF AGRICULTURE, BUREAU OF PLANT INDUSTRY.

2. THE PERCENTAGE OF PURE SEED PRESENT MILL REPRESENT THE FREEDOM OF SUCH AGRICULTURAL SEEDS FROM INERT MATTER AND OF THE SEEDS DISTINGUISMABLE BY THEIR APPEARANCE. THE PERCENTAGE OF CERMINATION SHOWN MILL BE ACTUAL SPRICITS AND ADMINISTRATION OF THE WORLD SHOWN SHOWN AND ADMINISTRATION OF THE WORLD BE ACTUAL SPRICITS AND ADMINISTRATION OF THE WORLD BE ACTUAL SPRICITS AND ADMINISTRATION OF THE WORLD BE ACTUAL SPRICITS AND MILL SEED PROPOSED UNDER THIS THE WILL BE SUBJECT TO ASSOCIATED STREAM OF PLANT MOUSTRY, AND MILL SEED THE WORLD STREAM OF PLANT MOUSTRY, AND MILL SEED THE MOST SECRET AND ADMINISTRATION OF SOMEWOOD ADMINISTRATION OF

3. ALL SEEDS WILL BE FURNISHED TO THE PROJECT SITE IN MIX PREPARED BY THE SEED PROCESSOR. THE MIX WILL HAVE A CERTIFICATION TAG THAT WILL BE PRESENTED TO THE LANDSCAPE ARCHITECT. SEED MIXTURES WILL BE AS FOLLOWS: FINE LAWN AREAS:

MIX TALL FESCUE PERENNIAL RYEGRASS

SHOWY NORTHEAST NATIVE WILDFLOWER MIX & SHEEP FESCUE AS SHOWN ON LANDSCAPE PLAN.

FACW WETLAND MEADOW MIX & REDTOP AS SHOWN ON LANDSCAPE PLAN. STARTER FERTILIZER:

MEADOW LAWN ARES

1. IMMEDIATELY BEFORE PERMANENT SEEDING, APPLY A STARTER FERTILIZER BY DISCING DOLOMITIC LIMESTONE AT A RATE OF 4 TONS PER ACRE, BASIC FERTILIZER (10-20-20) AT A RATE OF 100 LIS PER ACRE, MIO 25 LISS, OF 10-6-4, 50% ORGANIC NITROGEN PER THOUSAND SOURCE FEET (10.00 S. FT.). AT LEAST THIRTY-FIVE PERCENT (35%) OF THE TOTAL NITROGEN WILL BE WATER INSOLUBLE (NITROGEN FROM NATURAL ORGANIC SOURCES SUCH AS UREAFORM).

I, HAY OR STRAW MILDLE MUST BE APPLIED AT RATES OF AT LEAST 3.0 TONS PER ACRE. MULCH CONSISTING OF NATIVE OR RECOCCUTING GRASSES SUCH AS WELL FOR OUTS STRAW MILD BE PLACED OVER ALL LAWA AREAS WITHIN FORTY-EIGHT (46) AFTER TAKING GRASSES SUCH AS WELL FOR THE STRAW MILD BE PLACED OVER ALL LAWA AREAS WITHIN FORTY-EIGHT (47) AFTER THE STRAW MILD BE PLACED OVER ALL LAWA AREAS WITHIN FORTY AND ALL LAWA AREAS WITHIN F

2. PEGS AND TMME MAY BE USED TO SECURE MULCH. DRIVE BOHT—TO—TON—NOT (8" — 10") WOODEN PEGS TO MINEN TWO—TO—THREE NICHES (2" — 3") OF THE SOIL SURFACE EVERY FOUR FEET (4") IN ALL DIRECTIONS BEFORE OR AFTER APPLING MULCH. SECURE MULCH TO SOIL SURFACE BY STREICHMINI THIS EBETMEN PEGS IN A CRISS—CROSS WITHIN A SQUARE PATTERN. SECURE TWINE AROUND EACH PEG WITH TWO OR MORE ROUND TURNS.

3. EMULSIFIED ASPHALT MAY BE USED TO SECURE MULCH. EMULSION WILL CONFORM TO REQUIREMENTS OF AASHTO GRADE RS-PRINSTYANIA DEPARTMENT OF TRANSPORTATIONS BULLETIN NO. 25 FOR CLASS E-1 OR E-6. EMULSION WILL BE HOMOGENEOUS BE WISSIBLE WITH MATER. IT MILL CONTAIN NO SOLVETS OR OTHER BULLITY. AGENTS TOOK TO FLATH LIFE AND NOT WORTH PERCENT OF SAPONIFIRBLE ACIDS. APPLY UNIFORMLY AT THE RATE OF TWENTY-EIGHT (28) GALLONS PER ONE THOUSAND SQU. (1,000 SQL 10).

THE CONTRACTOR WILL, DURING THE LIFE OF THE CONTRACT, PROPERLY CARE FOR ALL AREAS AND MULCHES, PERFORMING SUCH MULCHING AS NECESSARY TO PROVIDE PROTECTION FOR ESTABLISHED GROWTH ON THE TREATED AREA.

RECYCLING & DISPOSAL METHODS

102.4(8)(5)(X) "PROCEDURES WHICH ENSURE THAT THE PROPER MEASURES FOR THE RECYCLING OR DISPOSAL OF MATERIALS ASSOCIATED WITH OR FROM THE PROJECT SITE WILL BE UNDEFTAKEN IN ACCORDANCE WITH DEPARTMENT FEGULATIONS."


DEP STANDARD CONSTRUCTION DETAIL #23
ROCK FILTERS - AASHTO #57 ROCK SECTION A-A

SEDIMENT MUST BE REMOVED WHEN ACCUMULATIONS REACH 1/2 THE HEIGHT OF THE FILTERS.


1" MIN.


SECTION B-B

IMMEDIATELY UPON STABILIZATION OF EACH CHANNEL, REMOVE ACCUMULATED SEDIMENT, REMOE ROCK FILTER, AND STABILIZE DISTURBED AREAS.



DEP STANDARD CONSTRUCTION DETAIL #16 ROCK CONSTRUCTION ENTRANCE







MAINTENANCE: ROCK CONSTRUCTION ENTRANCE THICKNESS SHALL BE CONSTANTLY MAINTAINED TO THE SPECIFIED DIMENSIONS BY ADDING ROCK. A STOCKPILE SHALL BE MAINTAINED ON SITE FOR THIS PURPOSE. AT THE END OF EACH CONSTRUCTION DAY, ALL SEDIMENT DEPOSITED ON PAVED ROZDWAYS SHALL BE REMOVED AND RETURNED TO THE CONSTRUCTION SITE.




DEP STANDARD CONSTRUCTION DETAIL #18
ROCK FILTER OUTLETS






SEDIMENT MUST BE REMOVED WHEN ACCUMULATIONS REACH 1/3 THE HEIGHT OF THE OUTLET.




USE R-FOR 2'- < D < 3' USE R-FOR 1'-< D < 2' USE R-2 SITE AND COMPREHENSIVE

CONSTRUCTION PLAN PHASES DRIVE TOWNSH COUNTY ALLEN ALLEN RLAND

32 OF 36






SIGHT DISTANCE METHODOLOGY.

1. MEW LOCATION: 10 FEET BACK FROM INTERSECTING CURB LINE, AT CENTERLINE OF STREET


2. MINIMUM REQUIRED SIGHT DISTANCE OF 200 FEET FOUND AND SIGHT LINE PLACED ON
INTERSECTION

3. METHCAL SIGHT DISTANCE FOUND ON PROFILE ASSUMING AN EYE HEIGHT OF 3.5 FT AND A
PARISCY PREDICT OF 2.0 FT, THIS DISTANCE WAS SO THAT THE ACTUAL HORIZONTAL SIGHT
PLACED SIGHT SIGHT SIGHT OF SIGHT SIGHT OF SIGHT SIGHT OF SIGHT SIGHT OF SIGHT DISTANCE.

4. ALL INTERSECTIONS HAVE SIGHT SIGHT OF SIGHT SIGHT OF SIGHT OF SIGHT OF SIGHT SIGHT OF SIGHT SIGHT OF SIGHT SIGHT OF SIGHT SIGHT



STABILIZE SINGHOLES IMMEDIATELY IF THEY ARE DISCOVERED. RUNOFF SHOULD NOT BE PERMITTED TO DIRECTLY EMTER ANY SINKHOLE OURING CONSTRUCTION. BERNIS AND/OR SWALES SHALL BE CONFIDENTED AND MANTAINED AROUND ALL SINKHOLES TO PREVENT SURVINE WATER FROM MANTAINED AROUND ALL SINKHOLES TO PREVENT SURVINE WATER FROM EMTERNISH AND/OR ACCUMULATING AROUND ANY SINKHOLE UNTIL IT HAS BEEN STABILIZED AND THE OVERLYING CONSTRUCTION IS COMPLETED.



BEDROCK.

AFTER THE SOIL IS CLEANED FROM THE ROCK, THE LOWER PORTION OF THE SINGHOLE SHOULD BE FILLED TO ABOVE THE LEVEL OF THE HIGHEST PINNACLE, BUT IN NO INSTANCE HIGHER THAN SIX (6) INCHES BELD WINGOU, WITH PADOT TYPE C OR BETTER COARSE AGGREGATE. A HEAVY DUTY WOVEN GEOTEXTILE MEMBRANE (TERRATEX HD OR HEAVY DUTY WOVEN GEOTEXTILE MEMBRANE (TERRATEX HD OR FLOUVALENT) SHOULD BE PLACED ON THE COARSE AGGREGATE IN A LOOSE AND UNSTRETCHED CONDITION. THE REJAINDER OF THE HOLE SHOULD BE FILLED WITH NATURE SOIL THAT IS PLACED IN LAYERS AND FINISHED WITH SIX (6) INCHES OF TOPSOIL THE LAYERS SHOULD BE NO MORE THAN SIX (6) NICHES NO TOPSOIL THE LAYERS SHOULD BE SIXULD BE CONFISCED TO 89 PERCENT OF THE MAXIMUM DRY SHOULD BE CONFISCED TO 89 PERCENT OF THE MAXIMUM DRY SHOULD BE CONFISCED TO 80 PERCENT OF THE MAXIMUM DRY SHOULD BE CONFISCED THE MOISTURE CONTENT OF THE SOIL SHOULD BE 2 PERCENT ATTER PLOCALISMY OF THE COTOSTILE MOMBRING IN A MANNER TO MINIMIZE SUPPAGE ON TEARING OF THE FABRIC.

TYPICAL SINKHOLE PLUGGING SCHEME NOT TO SCALE


AND SITE PLANNING ITECTURE LAND ARCH COMPREHENSIVE NSTRUCTION PLAN PHASES MGTON
MOUNT ALLEN
UPPER ALLEN
CUMBERLAND
PENNSYLVANIA AK S 34 OF 36





6" GATE VALVE


~ 6"PIPE

STEEL ANCHOR














SERVICE LATERAL - SHALLOW SEWER
























































35 OF 36

A FOR REV. DESC


□ ENGINEERING


□LANDSCAPE ARCHITECTURE


SITE PLANNING


AND

□ COMPREHENSIVE LAND









#57).


3. ALL PIPE SHALL BE SAME MATERIAL AS WATER MAIN.


6"PIPE—

1. PLACE CONCRETE ANCHORS AFTER FIRE HYDRANT HAS BEEN SET.

ISOLATION JOINT

UNDISTURBED EARTH





		-							
	Symbol	Quant	Botanical Name	Common Name	Caliper	Height	Spread	Root	Notes
	Trees								
	AR	9	Acer rubrum	Red Magle	2-2.5" CAI	12-14"	4.5	B/8	6 Br /Full head:
	FP	8	Fraxinus pennsylvanica	Green Ash	2-2.5" car	12-14"	4.5	BB	6 Br /Full heads
	PC	15	Platerus occidentals	American Sycamore	2-2 5" ca	12-14"	4-8	88	6 Br Full heads
	PS	43	Pinus strobus	White Pine		6-7	4-5	R/S	Full to ground
	TC	51	Tauge cenedensis	Hemiox		6-7	4.5	8/8	Full to ground
	Shrubs								- or or grown
Φ Θ –	HV	15	Hamemels virginians	Witch Heart		18-24	18-24"	3 gal	Full
o <u>o⊕ ⊖ -</u>	- IV	40	Bex verticitata	Winterperry		16-24"	16-24"	1 gar	Full
00-	- KL	8	Kalma latfolia	Mountain Laurei		18-24"	18-21"	3 gai	Full
0	- LB		Linders benasin	Spicetush		18-24"	18-24		Full
^	- RM	86	Phododendron mawnum	Rosebey		18-24	16-24"	3 gai	Full
0	EAF	41	Euonymus 2 Fireball	Burning Bush-Firebel		18-24"	16-24	B/B	Full

- A. LANDSCAPE WORK INCLUDES, BUT IS NOT LIMITED TO, THE FOLLOWING ITEMS:
- FURNISHING AND INSTALLATION OF LANDSCAPE MATERIALS, INCLUDING FERTILIZING AND MULCHING.

 SEEDING PER NOTES ON SEDIMENT AND EROSION CONTROL PLANS.

 WATERING BI-WEEKLY UNTIL FINAL ACCEPTANCE BY OWNER

 OF AN III
- ALTERNATE-MAINTENANCE FOR A PERIOD OF ONE (1) YEAR FROM FINAL ACCEPTANCE
 OF ALL PLANTING AND LAWNS
- B. THE CONTRACTOR SHALL PROVIDE ALL MATERIALS, LABOR, EQUIPMENT, TOOLS AND SERVICES REQUIRED TO ACCOMPLISH ALL RELATED WORK IN ACCORDANCE WITH THE DRAWINGS AND SPECIFICATIONS.
- C. WORK UNDER THIS CONTRACT SHALL ALSO INCLUDE THE FURNISHING AND PLACING OF ADDITIONAL TOPSOIL AS REQUIRED FOR PROPER IMPLEMENTATION OF PLANTING OPERATIONS.

- D. SOURCE QUALITY CONTROL:

 GENERAL: SHIP LANDSCAPE MATERIALS WITH CERTIFICATES OF INSPECTION REQUIRED BY GOVERNING AUTHORITIES. COMPLY WITH REQULATIONS APPLICABLE TO LANDSCAPE MATERIALS. DO NOT MAKE SUBSTITUTIONS: IF SPECIFIED LANDSCAPE MATERIAL IS NOT OBTAINABLE, SUBMIT PROOF OF NON-AVAILABILITY TO OWNER'S REPRESENTATIVE, THE PROOF OF NON-AVAILABILITY TO OWNER'S REPRESENTATIVE, THE PROOF OF SOURCE WITH MATERIAL.

 TOPSOILS AND STANDARDS: PACKAGE STANDARD PRODUCTS WITH MANUFACTURER'S CERTIFIED ANALYSIS.

 TOPSOILS AND STANDARDS: PACKAGE STANDARD PRODUCTS WITH MANUFACTURER'S CERTIFIED ANALYSIS.

 TOPSOILS AND STANDARDS: PACKAGE STANDARD PRODUCTS WITH MANUFACTURER'S CERTIFIED ANALYSIS.

 TOPSOILS AND STANDARD STORM OF THE TOP OF THE STANDARD PRODUCTS WITH MANUFACTURER'S CERTIFIED ANALYSIS.

 TOPSOILS AND STANDARD STANDARD FOR TURSERY SHOULD NAMES AND ADDRESSES OF OWNERS, DEPTH TO BE STRIPPED, CROPS GROWN AND FERT USED.

 TREES, SHRUBS AND PLANTS: PROVIDE TREES, SHRUBS, OURS APPLIED DURNIN, PAST 2 YEARS, DEPTIES, AND VARIETY SHOWN AND SCHEDULE FOR LANDSCAPE WORK AND COMPLYING WITH RECOVERY CROND STORM OF ANY SECON AND THE STANDARD STANDARD FOR NURSERY STOCK. PROVIDE HEALTHY, WORKDOWN ON AN REQUIREMENTS OF ANY SECON AND DEFECTS SUCH AS KNOTS, SUM—SCALD, INJURIES, ABRASIONS, OR DISFIGUREMENT, MESCON, SECON, SECORY OF THE AND ONE SHRUB OF EACH VARIETY WITH A SECURELY ATTACHED WATERPROOF TAG WITH BOTAINCAL AND COMMON NAME.

 INSPECTION: THE OWNER'S REPRESENTATIVE MAY INSPECT TREES AND SHRUBS EITHER AT PLACE OF GROWTH OR AT SITE BEFORE PLANTING FOR COMPLETION OF WORK. REMOVE REJECTO TREES ON DUALITY. UNDER SHAPPENDERS OF PLANTING FOR COMPLETION OF WORK. REMOVE REJECTOR TREES ON SHOW ON THE WORK OF THE WORK OF THE WATERIAL AT ANY TIME DURING PROCRESS OF WORK OF UPON NO PECFORM ON STREED BY COMPRISED BY COMPRISED AND PRESENT AND THESE OF INSPECTION OF WORK. REMOVE REJECTOR TREES OR SHAPPED THESE OF INSPECTION OF WORK. REMOVE REJECTOR TREES OR SHAPPED THESE OF INSPECTION OF WORK.
- E. CERTIFICATION: SUBMIT CERTIFICATES OF INSPECTION AS REQUIRED BY GOVERNMENTAL AUTHORITIES, AND MANUFACTURER'S OR VENDOR'S CERTIFIED ANALYSIS FOR SOIL AMENDMENTS AND FERTILIZER MATERIALS.
- PLANTING SCHEDULE: THE LANDSCAPE CONTRACTOR MUST SUBMIT A PROPOSED PLANTING SCHEDULE. ONCE ACCEPTED, REVISE DATES ONLY AS APPROVED IN WRITING, AFTER DOCUMENTATION OF REASONS FOR DELAYS.
- MAINTENANCE INSTRUCTIONS: THE CONTRACTOR SHALL PROVIDE TYPED INSTRUCTIONS RECOMMENDING PROCEDURES TO BE ESTABLISHED BY OWNER FOR MAINTENANCE OF LANDSCAPE WORK FOR ONE FULL YEAR. SUBMIT PRIOR TO ACCEPTANCE.
- DELIVER TREES AND SHRUES AFTER PREPARATIONS FOR PLANTING HAVE BEEN COMPLETED AND PLANT IMMEDIATELY. IF PLANTING IS DELAYED MORE THAN 6 HOURS AFTER DELIVERY, SET TREES AND SHRUBS IN SHADE, PROTECT FROM WEATHER AND MECHANICAL DAMAGE, AND KEEP ROOTS MOIST BY COVERING WITH MUICH.
- I. DO NOT REMOVE CONTAINER-GROWN STOCK FROM CONTAINERS UNTIL PLANTING TIME.
- UTILITIES: DETERMINE LOCATIONS OF UNDERGROUND UTILITIES AND PERFORM WORK IN A MANNER WHICH WILL AVOID POSSIBLE DAMAGE. HAND EXCAVATE AS REQUIRED. MAINTAIN GRADE STAKES SET BY OTHERS UNTIL REMOVAL IS MUTUALLY AGREED UPON BY PARTIES CONCERNED.
- K. EXCAVATION: WHEN CONDITIONS DETRIMENTAL TO PLANT GROWTH ARE ENCOUNTERED NOTIFY OWNER'S REPRESENTATIVE BEFORE PLANTING.
- PLANTING TIME: PROCEED WITH, AND COMPLETE LANDSCAPE WORK AS RAPIDLY AS PORTIONS OF SITE BECOME AVAILABLE, WORKING WITHIN SEASONAL LIMITATIONS. PLANT OR INSTALL MATERIALS DURING NORMAL PLANTING SEASONS FOR EACH TYPE.
- M. COORDINATION WITH LAWNS: PLANT TREES AND SHRUBS AFTER FINAL GRADES ARE ESTABLISHED AND PRIOR TO PLANTING OF LAWNS UNLESS OTHERWISE ACCEPTABLE TO OWNER'S REPRESENTATIVE. IF PLANTING OCCURS AFTER LAWN WORK, PROTECT LAWN AREAS AND PROMPTLY REPAIR DAMAGE TO LAWNS RESULTING FROM PLANTING OPERATIONS.
- MAINTAIN TREES AND SHRUBS THROUGH SPECIFIED MAINTENANCE PERIOD OR UNTIL THE DATE OF FINAL ACCEPTANCE, WHICHEVER IS LONGER. THE DATE OF FINAL ACCEPTANCE IS DEFINED AS THE INSPECTION REQUESTED BY THE CONTRACTOR AFTER THE LAST OF THE TOTAL PLANTING IS INSTALLED AND MULCHED, AND AT WHICH TIME ALL CONDITIONS ARE ACCEPTABLE TO THE OWNER AND THE OWNER'S REPRESENTATIVE.
- ALTHOUGH PERIODIC REQUEST FOR PAYMENT WILL BE ACCEPTED, THEIR INDIVIDUAL APPROVAL AND SUBSEQUENT PAYMENT SHALL NOT ACTIVATE THE GUARANTEE PERIOD UNTIL ALL PLANTS ARE IN PLACE AND INSPECTED BY THE OWNER AND THE OWNER'S REPRESENTATIVE.
- WARRANTY TREES AND SHRUBS, FOR A PERIOD OF ONE YEAR AFTER DATE OF FINAL ACCEPTANCE, AGAINST DEFECTS INCLUDING DEATH AND UNSATISFACTORY GROWTH, EXCEPT FOR DEFECTS RESULTING FROM NEGLECT BY OWNER, ABUSE OR DAMAGE BY OTHERS, OR UNUSUAL PHENOMENA OR INCIDENTS WHICH ARE BEYOND LANDSCAPE INSTALLER'S CONTROL.
- REMOVE AND REPLACE TREES, SHRUBS, OR OTHER PLANTS FOUND TO BE DEAD OR IN UNHEALTHY CONDITION DURING WARRANTY PERIOD. MAKE REPLACEMENTS DURING GROWTH SEASON FOLLOWING END OF WARRANTY PERIOD. REPLACE TREES AND SHRUBS WHICH ARE IN DOUBTFUL CONDITION AT END OF WARRANTY PERIOD KINLESS, IN OPINION OF THE OWNER'S REPRESENTATIVE, IT IS ADVISABLE TO EXTEND WARRANTY PERIOD FOR A FULL GROWING SEASON.
- R. ON-SITE TOPSOIL MAY BE USED FOR PLANTING OPERATION. ADDITIONAL TOPSOIL FOR PLANTING BACKFILL MUST BE FURNISHED BY LANDSCAPE CONTRACTOR FROM AN APPROVED OFF-SITE SOURCE.
- PROVIDE NEW TOPSOIL THAT IS FERTILE, FRIABLE, NATURAL LOAM, SURFACE SOIL, FREE OF SUBSOIL, CLAY LUMPS, BRUSH, WEEDS AND OTHER LITER, AND FREE OF ROOTS, STUMPS, STONES LARGER THAN 1 INCH IN ANY DIMENSION, AND OTHER EXTRANEOUS OR TONC MATTER HARMFUL TO PLANT GROWN! IN ACCORDANCE WITH ASAFTO DESIGNATION.
- OBTAIN TOPSOIL FROM LOCAL SOURCES OR FROM AREAS HAWING SUITABLE SOIL CHARACTERISTICS. OBTAIN TOPSOIL
 ONLY FROM NATURALLY, WELL-DRAINED SITES WHERE TOPSOIL OCCURS IN A DEPTH OF NOT LESS THAN 4 INCHES.
 DO NOT OBTAIN FROM BOGS OR MARSHES. TOPSOIL SHALL HAVE MINIMUM FIVE (5%) PERCENT ORGANIC MATERIAL BY
 WEIGHT.
- ALL MATERIAL UNSUITABLE FOR USE AS TOPSOIL AND ACCUMULATED AS PART OF THE LANDSCAPE CONTRACT SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND SHALL BE EXPEDITIOUSLY REMOVED FROM THE SITE.
- SOIL AMENDMENTS
 LIME: NATURAL DOLOMITIC LIMESTONE CONTAINING NOT LESS THAN 85 PERCENT OF TOTAL CARBONATES WITH A
 MINIMUM OF 30 PERCENT MAGNESIUM CARBONATES, GROUND SO THAT NOT LESS THAN 90 PERCENT PASSES A
 10—MESH SIEVE AND NOT LESS THAN 50 PERCENT PASSES A 100—MESH SIEVE.
- PEAT: PEAT SHALL BE SPHAGNUM PEAT MOSS. IT SHALL BE FINELY SHREDDED, CONSIST OF 100% ORGANIC PEAT, BE BROWN IN CALOR, AND SUITABLE FOR HORTICULTURAL PURPOSES. PEAT SHALL BE MEASURED IN AIR DRY CONDITIONS, CONTAINING NOT MORE THAN THIRTY-FIVE PERCENT (35%) MOISTURE BY WEIGHT.
- BONEMEAL: COMMERCIAL, RAW, FINELY GROUND; 4 % N & 20 % PHOSPHORIC ACID.
- SUPERPHOSPHATE: SOLUBLE MIXTURE OF TREATED MINERALS; 20 %PHOSPHORIC ACID.
- VERMICULITE: HORTICULTURAL GRADE, FREE OF TOXIC SUBSTANCES.
- COMMERCIAL FERTILIZER: SHALL BE A COMPLETE FORMULA AND SHALL CONFORM TO ALL REQUIREMENTS OF THE PENNSYLVANIA FERTILIZER ACT OF 1965. IT SHALL BE UNIFORM IN COMPOSITION, DRY AND FREE-FLOWING, AND SHALL BE DELIVERED TO THE STE! IN THE ORIGINAL, UNDOPENED CONTAINER WITH MANUFACTURER'S GUARANTEED ANALYSIS. ANY FERTILIZER THAT BECOMES CAKED OR OTHERWISE DAMAGED WILL NOT BE ACCEPTED. COMMERCIAL FERTILIZER SHALL BE IN PELLETED OR GRANULAR FORM AND SHALL BE OF THE FOLLOWING RATIONS: 10-20-20, OR APPROVED EQUAL.
- MYCOR: MYCOR'® TREE SAVER® (MYCORRHIZAL TRANSPLANT INOCULANT) SHALL BE INCLUDED WITH ALL PLANTINGS EXCEPT ERICACEOUS PLANTS (RHODODENDRONS, AZALEAS AND LAURELS) AT THE MANUFACTURER'S RECOMMENDED RATES. MYCOR TREATS THE ROOT ZONE WITH BENEFICIAL MYCORHIZAL FUNGI, WATER ABSORBENT HYROGELS AND ORGANIC SOIL CONDITIONERS.
- GYPSUM SHALL BE AS COMMERCIALLY AVAILABLE FOR PLANTING USES.
- ANTIDESICCANT SPRAY SHALL BE "WILT PRUF", AS MANUFACTURED BY NURSERY SPECIALTY PRODUCTS, GREENWICH, CONNECTICUT, OR APPROVED EQUAL.
- U. MULCH: SHALL BE SHREDDED DAK TREE BARK, BROWN IN COLOR, PH OF FOUR TO FIVE AND FREE OF HARMFUL MINERAL MATTER. A NATURAL MOISTURE CONTENT OF 15-40%, AND COARSE TEXTURE: ONE-HALF INCH (1/2") TO TWO INCH (2") DIAMETER.
- WOODEN STAKES SHALL BE 2" X 2" X 8' LENGTH, MINIMUM.
- MINIMUM OF TWELVE-GAUGE, MULTI-STRANDED, GALVANIZED STEEL WIRE. WIRE SHALL NOT COME IN CONTACT WITH THE PLANT. IT SHALL BE COVERED WITH RUBBER HOSE.

- W. BACKFILL SHALL CONSIST OF FIFTY PERCENT (50%) EXISTING SOIL, TWENTY-FIVE PERCENT (25%) NEW TOPSOIL AND TWENTY-FIVE PERCENT (25%) PEAT MOSS AS SPECIFIED WITH MYCOR" ADDED PER MANUFACTURER RECOMMENDATION BASED ON ROOT BALL SIZE. READ MANUFACTURER LITERATURE FOR ERICACEOUS PLANTS THAT SHALL NOT RECEIVE MYCOR AND INCLUDE A WATER ABSORBENT HYDROGEL ONLY WITH THOSE PLANTS.
- ALL PLANTS SHALL BE NURSERY GROWN TRUE TO TYPE AND NAME IN ACCORDANCE WITH THE LATEST EDITION OF "STANDARDIZED PLANT NAMES," AMERICAN JOINT COMMITTEE ON HORTICULTURAL NOMENCLATURE. ALL PLANTS SHALL BE WELL-BRANCHED, NOGROUS AND BALANCED ROOT AND TOP GROWTH AND NO. I GROWED. THEY SHALL BE FREE FROM DISEASE, INSECTS, MECHANICAL WOUNDS, BROKEN BRANCHES, DECAY OR ANY OTHER DEFECT. EACH SPECIES SHALL CONFORM TO "AMERICAN STANDARD OF NURSERY STOCK," AS DEVELOPED BY THE AMERICAN ASSOCIATION OF NURSERYMEN, INC. AND APPROVED BY THE AMERICAN STANDARDS ASSOCIATION, INC.
- PROVIDE FRESHLY DUG TREES AND SHRUBS. DO NOT PRUNE PRIOR TO DELIVERY. DO NOT BEND OR BIND—TIE
 TREES OR SHRUBS IN SUCH A MANNER AS TO DAMAGE BARK, BREAK BRANCHES OR DESTROY NATURAL SHAPE
 PROVIDE PROTECTIVE COVERING DUBING DELIVERY.
- ALL ACCEPTED PLANTING STOCK, IF NOT PLANTED IMMEDIATELY, SHALL BE HEELED—IN OR STORED. STOCK LEFT OUT OF THE GROUND UNPROTECTED OVERNIGHT, LEFT WITH ROOTS EXPOSED TO HEAT OR FREEZING, OR OTHERWISE UNPROTECTED DURING TRANSIT, UNLOADING, HEELING—IN, OR PLANTING, WILL BE REJECTED.
- Y. HERBICIDE:
- PRE-EMERGENT HERBICIDE SHALL BE SURFLAN AS MANUFACTURED BY DOW ELANCO.
- POST-EMERGENT HERBICIDE SHALL BE DESIGNED FOR AQUATIC USE WITH NO RESTRICTIONS ON WATER USE, SPECIFICALLY DOMESTIC USE, AFTER APPLICATION. STANDARD OF QUALITY SHALL BE RODEO AS MANUFACTURED BY MONSANTO, BOO NO. LINDBERGH BOULEVARD, ST. LOUIS, MO 63167, (314) 694-0100.
- ALL SHRUB MASSES SHOWN ON THE DRAWINGS SHALL BE CONTAINED WITHIN A CONTINUOUS BED FOR EACH MASS PLANTING. AS SUCH, THE BED SHALL BE STRIPPED OF TURF AND THE ENTIRE BED CULTIVATED BY ROTOTILING OR PLOWING AND DISCING SO THAT THE ENTIRE SURFACE IS TILLED TO A MIN DEPTH OF EIGHT INCHES (8").
- AA. PITS FOR PLANTING SHRUBS SHALL BE DUG LARGE ENOUGH TO ACCOMMODATE THE ROOTS AND PLANTS WITHOUT CROWDING AND SHALL BE OF CORRECT DEPTH TO ALLOW PLACEMENT OF PLANT AT PROPER DEPTH ON SUBGRADE BEFORE BACKFILLING.
- THE DIAMETER OF THE PLANT PIT SHALL BE AT LEAST TWICE THE DIAMETER OF THE PLANT ROOT BALL WITH AT LEAST SIX INCHES (6") OF OPEN EXCAVATION BETWEEN THE ROOT BALL AND THE VERTICAL WALL OF THE PIT IN ALL DIRECTIONS. REFER TO THE PLANTING DETAILS FOR PURTHER INFORMATION.
- PITS FOR LARGER PLANTS, SUCH AS DECIDIOUS SHADE TREES AND EVERGREENS, SHALL BE OF SUFFICIENT DEPT TO ALLOW THE PLACING OF ROOT BALL ON SUBGRADE PRIOR TO BACKFILLING. FURTHER, THE DIAMETER OF THE PLANT PIT SHALL BE AT LEAST TWICE THE DIAMETER OF THE PLANT ROOT BALL WITH AT LEAST TWELVE INCHES (12") OF OPEN EXCAVATION BETWEEN THE ROOT BALL AND THE VERTICAL WALL OF THE PIT IN ALL DIRECTIONS. REFER TO PLANTING DETAILS FOR FURTHER INFORMATION.
- DIGGING OPERATIONS, PARTICULARLY ON SLOPES, SHALL BE PLANNED IN ORDER THAT ACTUAL PLANTING OPERATIONS WILL FOLLOW WITHIN TWENTY-FOUR (24) HOURS.
- PLANTING AREAS EXCEPT FOR THE BEDS WITH GROUNDCOVER, BULBS, PERENNIALS OR SEASONAL COLOR SHALL BE CONSIDERED TO HAVE SUFFICIENT TOPSOIL FOR THE BECKENT TOPSOIL REQUIRED WITHIN EACH PLANT PIT FOR THE BACKFILL MIX SHALL BE FURNISHED AND PLACED BY THE CONTRACTOR.
- BALLED AND BURLAPPED PLANTS SHALL BE HANDLED BY THE EARTH BALL AND NOT BY THE PLANT ITSELF AND
 SHALL BE PLACED IN THE PITS WITHOUT REMOVING THE BURLAP, AFTER WHICH THE BURLAP SHALL BE LAID BACK
 FROM THE BALL. PLANTING DPERATIONS SHALL CONFORM TO PLANTING DETAILS SET FORTH ON APPROPRIATE
 ACCOMPANYING DRAWINGS.
- BACKFILL MIX, SHALL BE MIXED IN BULK AND SHALL NOT BE MIXED IN THE INDIVIDUAL PLANT PIT. THE BACKFILL MIX SHALL BE WORKED AROUND THE BALL AND BE FIRMLY TAMPED AND/OR PUDDLED AS BACKFILLING PROGRESSES OF FILL ALL VOIDS AND TO ELIMINATE AIR POCKETS. EXCESS EXCAVATION FROM PLANT PIT, STICKS, SOD, CLODS OR OTHER MATERIAL THAT WOULD DECOMPOSE AND FORM AIR POCKETS IN THE PLANTING MEDIA SHALL BE REMOVED. PLACE BACKFILL IN SIX-INCH (6") INCREMENTS OF DEPTH.
- ON LEVEL GROUND AND ON RELATIVELY GENTLE SLOPES, A SHALLOW BASIN, THE DIAMETER OF THE PLANT PIT. SHALL BE LET AROUND EACH PLANT. ON STEEP SLOPES, SUFFICIENT SOIL SHALL BE PULLED TO THE LOWER SIDE OF THE PLANT TO FORM A SHALLOW BASIN TO CATCH AND HOLD WATER. EXCAVATED MATERIALS FROM PLANT PITS MAY BE USED FOR FOUR INCH (4°) HIGH BERMS TO CREATE BASINS AROUND EACH TREE PIT OR SHRUB. SHRUBS IN BED AREAS SHALL NOT HAVE INDIVIDUAL SAUCERS OF BASINS.

AFTER PLACING BACKFILL, PRIOR TO FINAL WATERING AND BEFORE MULCHING, APPLY FERTILIZER TO ALL PLANTS AT THE FOLLOWING RATES. APPLY FERTILIZER EVENLY OVER ENTIRE PLANT PIT TO AVOID FERTILIZER BURN.

EVERGREEN TREE
SHADE TREE
SHADE TREE
DECIDIOUS SHRUB
EVERGREEN SHRUB
FLOWERING TREE
ORNAMENTAL GRASS
BILLIBS
GROUND COVER
CROUND COVER
PERENNIALS

ONE = EIGHTH (1/8) POUND PER FOOT OF HEIGHT
ONE (1) POUND PER INCH OF CALIPER
ONE (1) POUND PER 100 SQUARE FEET.
ONE (1) POUND PER 100 SQUARE FEET.
ONE (1) POUND PER 100 SQUARE FEET.

DAMAGED OR BROKEN MAIN ROOTS SHALL BE PRUNED WITH A CLEAN OBLIQUE CUT IMMEDIATELY ABOVE THE POINT OF DAMAGE.

AC. ALL DECIDUOUS AND EVERGREEN TREES SHALL BE STAKED AND GUYED IMMEDIATELY AFTER BACKFILLING AS SHOWN ON THE ACCOMPANYING DRAWINGS.

- AD. THE TOPS OF ALL DECIDIOUS STOCK SHALL BE PRUNED AT THE TIME OF PLANTING OR IMMEDIATELY THEREAFTER TO THE BEST HORTICULTURAL PRACTICES WITH RESPECT TO NATURAL FORM OF THE INDIVIDUAL SPECIES. A SINGLE TERMINAL LEADER SHALL BE PRESERVED WHEN PRUNING DECIDIOUS SHADE TREES. UNLESS OTHERWISE DIRECTED BY THE OWNER'S REPRESENTATIVE, ALL DECIDIOUS PLANTS SHALL HAVE ONE—THIRD (1/3) OF THE POTENTIAL LEAF—BEARING SURFACE REMOVED.
- AC. ALL PLANTS SHALL BE THOROUGHLY WATERED BI-WEEKLY (AT A MINIMUM) IN A MANNER SATISFACTORY TO THE OWNER'S REPRESENTATIVE DURING THE CONSTRUCTION PERIOD AND UNTIL FINAL ACCEPTANCE. ALL NECESSARY TANK TRUCKS, HOSES, AND APPURTENANCES SHALL BE PROVIDED BY THE CONTRACTOR.
- AD. ALL PLANTS SHALL BE MULCHED WITH SPECIFIED MULCH TO A UNIFORM DEPTH OF THREE INCHES (3"), PLACED AFTER PLANTING. TREE PITS SHALL BE MULCHED TO THE OUTER EDGE OF THE EARTH BERM. APPLY MULCH WITHIN TWO (2) DAYS AFTER PLANTING, EXCEPT IN THE CASE OF WINTER PLANTING WHEN MULCH SHALL BE PLACED IMMEDIATELY.
- AE. THE CONTRACTOR SHALL GUARANTEE ALL PLANTS FOR A PERIOD OF ONE (1) YEAR FROM DATE OF FINAL ACCEPTANCE. DATE OF FINAL ACCEPTANCE IS DEFINED AS THE DATE OF COMPLETION AND ACCEPTANCE OF ALL PUNCH LIST ITEMS FROM THE INSPECTION REQUESTED BY THE CONTRACTOR AFTER THE LAST OF THE TOTAL PLANTING IS INSTALLED AND MULCHED, AND AT WHICH TIME ALL CONDITIONS ARE ACCEPTABLE TO THE OWNER AND
- IF A PLANT DIES AFTER FINAL ACCEPTANCE, IT SHALL BE REMOVED AND REPLACED IMMEDIATELY OR, IN THE CASE OF PLANTS REQUIRING PROPER SEASONAL PLANTING, REPLACEMENT IN THE NEXT APPROPRIATE SEASON, EVEN IF THAT SEASON FALLS BEYOND THE ONE-YEAR GUARANTEE PERIOD.
- WHERE A LARGE PORTION OF A PLANT DIES BACK CAUSING A PERMANENT OR LONG-TERM DEFORMITY, IT SHALL BE REPLACED.
- ANY DELAY ON THE PART OF THE CONTRACTOR TO REMOVE AND REPLACE UNSATISFACTORY MATERIALS SHALL CAUSE THE OWNER TO HAVE SUCH WORK PERFORMED AND THE CONTRACTOR SHALL BE BACKCHARGED FOR THAT WORK.
- PLANT REPLACEMENT SHALL BE PERFORMED AS MANY TIMES AS NECESSARY IN A SINGLE LOCATION; THE GUARANTEE DOES NOT LIMIT REPLACEMENT TO "ONE TIME".
- REPLACEMENT SHALL BE OF EXACT TYPE, SPECIES AND SIZE AS ORIGINALLY SPECIFIED.
- THE CONTRACTOR SHALL, IN ADDITION TO REPLACEMENT OF UNSATISFACTORY PLANT MATERIALS, MAKE GOOD ALL DAMAGE TO THE STRUCTURES AND GROUNDS OR EQUIPMENT AND CONTENTS THEREOF IF SUCH UNSATISFACTORY CONDITION OR DAMAGE DEVELOPS WITHIN THE STIPULATED PERIOD DUE TO THE MATERIALS OR WORKMANSHIP WHILL ARE INFERIOR, DEFECTIVE OR NOT IN ACCORDANCE WITH THIS CONTRACT, AND MUST MAKE GOOD ANY WORK OR MATERIALS OR GROUNDS WHICH ARE DISTURBED IN FULFILLING THE REQUIREMENTS OF THIS GUARANTEE.
- AT THE END OF THE ONE-YEAR GUARANTEE PERIOD, THE CONTRACTOR SHALL REMOVE ALL GUYING MATERIALS.
- AF. DURING THE CONTRACT AND AT INTERVALS AS DIRECTED BY THE OWNER'S REPRESENTATIVE AND AS THE LANDSCAPE WORK IS COMPLETED. CLEAR THE SITE OF ALL EXTRANEOUS MATERIALS INCLUDING QUANTITIES OF SUBSOIL, ROCK, OTHER SPOILS REMAINING FROM EXCAVATION AFTER PLANTING, RUBBISH OR DEBRIS, AND LEAVE ALL PLANTING SITES IN A CLEAN, SAFE, NEAT, CONDITION.
- AG. MAINTAIN ALL PLANTING FROM TIME OF ARRIVAL ON SITE UNTIL INSPECTION AT TIME OF FINAL ACCEPTANCE.

PLAN LAND COMPREHENSIVE 11 DRIVE TOWNSHIP COUNTY FINAL - PHASE ONE & TW
PENNINGTON
LOCATION: MOUNT ALLEN D
UPPER ALLEN D
CUMBER ALLEN OF
PENNSYLVANIA
LANDSCAPE DETAILS

9

36 OF 36