

VILLAGE OF CHERRY VALLEY

Village of Cherry Valley Work in ROW Permit

The Village of Cherry Valley grants permission to _____
Company Name

to excavate within the right-of-way in front of _____
Address of excavation

OR, you may attach a map of the ROW you are requesting permission to work in, along with construction date(s). This work is for the purpose of _____

In return the following conditions must be met:

1. Any residents that may be affected by any construction associated with the job listed above, will be notified of that road closure a minimum of 48 hours in advance. All appropriate traffic control measures, road closure signs and barricades will be erected in accordance with MUTCD standards.
2. The Village must be notified, by the contractor, a minimum of 48 hours prior to start of the work. Inspections must be made by the Village to verify conformance with this permit.
3. Any excavated area, that is to have a road surface, driveway, driveway apron or sidewalk placed over it, must be backfilled with washed bedding chips. A minimum of 10 inches of compacted CA6 will be required between the bedding chips and final hard surface.
4. Any curb that is removed or undermined will be replaced in kind.
5. The extent of roadway pavement repairs will be determined by the Public Works Director regardless of the actual disturbed area. All edges of the existing pavement will be saw cut to the full depth of the pavement to create a clean and level joint.
6. A minimum of 3 inches of HMA Surface Course N50, Mix D, placed in two lifts, shall be used to complete a bituminous driveway apron or roadway repair. Lateral cuts only, no square cut-outs in roadways or bike paths.

VILLAGE OF CHERRY VALLEY

7. Any sidewalk and curb that needs to be replaced shall retain the same width as the existing neighborhood standards in order to promote continuity within each neighborhood. A minimum of a six-bag mix shall be required for all cast concrete. All sidewalks, irrespective of their location shall have a thickness of not less than five (5) inches. All sidewalks must be approved by the Public Works Director or the designated engineer prior to their construction. All sidewalks constructed and/or installed which cross driveways, shall have a minimum thickness of six (6) inches.
8. Restoration of excavated areas within the Right of Way shall be restored to same or better condition than prior to excavation. Grassy areas must have topsoil and seed, along with erosion control matting.
9. Utilities cannot be installed within 5 feet of Water Main, unless authorized by the Public Works Director.
10. A Performance Bond, in the amount of \$1,000.00, will be required before the permit will be issued.
11. When work is completed The Village of Cherry Valley must be contacted for inspection by the Public Works Department and to pick up your performance bond.

Any deviation from this permit may result in the rejection of the work. The contractor agrees to redo any work rejected by the Village at no cost to the Village.

Village of Cherry Valley

Date of Approval

The Village of Cherry Valley 806 E. State St. Cherry Valley Illinois 61016
Ph: 815-332-3441
Fax: 815-332-3414